



Motor Oil C2 5W-30

Product Code: 76140

Synthetic MID SAPS Passenger Car Motor Oil

Motor Oil C2 5W-30 is a high performance fuel saving MID SAPS engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a PSA B71 2290 specification is required and suitable for all engines which require an ACEA A5/B5, C2 performance specification

Motor Oil C2 5W-30 is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

Motor Oil C2 5W-30 exceeds the following performance criteria:

Meets:	ACEA C2	API SN/CF	ACEA A5/B5
	ACEA A1/B1	PSA B71 2290	Renault 0700

Suitable for use: IVECO 18-1811 SC1

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J 300	5W-30
Density @15°C	kg/m ³	ASTM D4052	850
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	61
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	10.6
Viscosity Index		ASTM D2270	165
Viscosity CCS -30°C	cP	ASTM D5293	5600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	7.8
Sulphated Ash	%Wt	ASTM D874	0.79

Date Issued: 23-09-2022	Supersedes: 23-02-2021	Revision Nr.: 03
-------------------------	------------------------	------------------