

Motor Oil Semi Synth SL 10W-40

Synthetic technology Passenger Car Motor Oil

Motor Oil Semi Synth SL 10W-40 is an universal high performance synthetic technology oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

Product Code: 78130

Motor Oil Semi Synth SL 10W-40 is formulated with high quality re-refined base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Motor Oil Semi Synth SL 10W-40 exceeds the following performance criteria:

ACEA SL/CF ACEA A3/B3 MB 229.1 VW 501.01

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W-40
Density @15°C	kg/m³	ASTM D4052	861
Kin. Viscosity @40°C	mm²/s	ASTM D7042	92
Kin. Viscosity @100°C	mm²/s	ASTM D7042	14.2
Viscosity Index		ASTM D2270	159
Viscosity CCS @-25	сР	ASTM D5293	4800
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	8.3

| Date Issued: 10-10-2022 | Supersedes: 12-05-2021 | Revision Nr.: 05