



Classic SAE 50

Product Code: 79020

Mineral Engine oil with additional Zinc Antiwear Additives

Classic SAE 50 is a 100% high quality mineral mono-grade SAE 50 oil for gasoline engines especially formulated with supplementary Zinc additives and suited for use in classic cars.

Classic SAE 50 is based on high quality virgin mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Very good lubrication of engine parts.
- Excellent protection against wear.
- High protection against corrosion.
- Good protection against wear, foam en corrosion.
- No danger of encrusted dirt becoming unstuck.
- Compatible with classic seals and rubbers.

Classic SAE 50 exceeds the following performance criteria:

API: SF/CD

Typical Analysis

| Properties | Unit | Method | Typical Value |
|-----------------------|--------------------|------------|---------------|
| SAE Grade | | SAE J300 | 50 |
| Density @15°C | kg/m ³ | ASTM D4052 | 902 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 220 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 18.9 |
| Viscosity Index | | ASTM D2270 | 95 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -15 |
| Total Base Number | mgKOH/g | ASTM D2896 | 6.0 |
| Zinc content | ppm | ASTM D6443 | 2300 |

| | | |
|-------------------------|------------------------|------------------|
| Date Issued: 23-02-2021 | Supersedes: 25-08-2015 | Revision Nr.: 01 |
|-------------------------|------------------------|------------------|