



Motor Oil Mineral BC SL/CF 15W-40

Product Code: 79040

Mineral Passenger Car Motor Oil

Motor Oil Mineral BC SL/CF 15W-40 is an universal high performance oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

Motor Oil Mineral BC SL/CF 15W-40 is formulated with high quality refined mineral base stocks in combination with a special additive technology to achieve the following performance:

- Good low temperature properties.
- Protection to wear by cold start.
- High thermal- and oxidation stability.
- Good resistance against foaming, corrosion and wear.
- Good dispersancy and detergency level.
- High viscosity index.

Motor Oil Mineral BC SL/CF 15W-40 exceeds the following performance criteria:

API SL/CF

ACEA A3/B4-08

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	15W-40
Density @15°C	kg/m ³	ASTM D4052	871
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	100
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	143
Viscosity CCS @-20°C°	cP	ASTM D5293	4500
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	6.8

Date Issued: 23-02-2021	Supersedes: 01-07-2015	Revision Nr.: 01
-------------------------	------------------------	------------------