

Motor Oil Synthetic SN 10W-40

Product Code: 79050

Motor Oil Synthetic SN 10W-40 is an universal high performance fuel saving synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for engines equipped with a Particulate Filter.

Motor Oil Synthetic SN 10W-40 is formulated with high quality synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Motor Oil Synthetic SN 10W-40 meets the following performance criteria:

| Approved | MB-Approval 229.3 | | |
|----------|------------------------|--------------------------------|----------|
| Meets | API SP RN 0700/0710 | ACEA A3/B4 VW 501.01/505.00 | MB 226.5 |

Typical Analysis

| Properties | | Unit | Meth | od | Typical Value |
|-------------------------|-------------------|---------------|------------|------------|---------------|
| | | | | | |
| SAE Grade | | | SAE J300 | | 10W-40 |
| Density @15°C | kg/m ³ | ASTM D4052 | | 859 | |
| Kin. Viscosity @40°C | mm²/s | ASTM D7042 | | 91.3 | |
| Kin. Viscosity @100°C | mm²/s | ASTM D7042 | | 13.7 | |
| Viscosity Index | | ASTM D2270 | | 153 | |
| Viscosity CCS @-25°C | cP | ASTM | 1 D5293 | 6600 | |
| Flash Point COC, min | °C | ASTM D92 | | >215 | |
| Pour Point | | °C | ASTM D7346 | | -33 |
| Total Base Number | | mgKOH/g | ASTM D2896 | | 10.9 |
| Sulphated Ash | | %Wt | ASTM | 1 D874 | 1.3 |
| | | | | | |
| Date Issued: 03-08-2022 | Supersede | s: 25-02-2021 | | Revision N | lr.: 05 |