

Motor Oil Longlife-III Synthetic 0W-30

Product Code: 79370

Fully Synthetic LOW SAPS Passenger Car Motor Oil

Motor Oil Longlife-III Synthetic OW-30 is a high performance fuel saving LOW SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm VW 504.00/507.00 has been prescribed.

<u>Remark: not suitable for R5- en V10 TDI engines and engines where VAG norm</u> <u>VW 506.01 is being advised.</u>

Motor Oil Longlife-III Synthetic OW-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

Motor Oil Longlife-III Synthetic 0W-30 meets the following performance criteria:

ACEA C3-16 VW 504.00/507.00 Porsche C30

Typical Analysis

Properties		Unit Me		od	Typical Value	
SAE Grade			SAE 2	1300	0W-30	
Density @15°C		kg/m ³	ASTM	I D4052	844	
Kin. Viscosity @40°C		mm²/s	ASTM	I D7042	63	
Kin. Viscosity @100°C		mm²/s	ASTM D7042		12.2	
Viscosity Index			ASTM	I D2270	194	
Viscosity CCS @-35°C		сР	ASTM	I D5293	5900	
Flash Point COC		°C	ASTM D92		210	
Pour Point		°C	ASTM D7346		-48	
Total Base Number		mgKOH/g	ASTM D2896		8.2	
Sulphated Ash		%Wt	ASTM D874		0.7	
			•			
Date Issued: 26-02-2021	Supersede	Supersedes: 15-09-2020			Revision Nr.: 02	