

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form	: Mixture
Product name	: 79060 - Motor Oil Mineral Plus SN 15W-40
Product code	: 79060
Type of product	: Lubricant

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Industrial/Professional use spec	: Industrial For professional use only
Function or use category	: Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Transnational Blenders B.V.  
Wieldrechtseweg 37  
3316 BG Dordrecht - Netherlands  
T +31 (0)78 6527652  
[technical@tnb.nl](mailto:technical@tnb.nl) - [www.tnb.nl](http://www.tnb.nl)

#### 1.4. Emergency telephone number

Emergency number	: +31 (0)78 6527652 Monday to Friday: 09:00 - 16:00 (CET)
------------------	--

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU > 2015: According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)**

Not classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements	: EUH210 - Safety data sheet available on request.
----------------	--

#### 2.3. Other hazards

Other hazards which do not result in classification	: Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.
---	---

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	≥ 75	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	1 – 2.5	Not classified
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	CAS-No.: 84605-29-8 EC-No.: 283-392-8 REACH-no: 01-2119493626-26	0.5 – 2.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	EC-No.: 701-251-5 REACH-no: 01-2119524004-56	0.5 – 2.5	Aquatic Chronic 4, H413

#### Specific concentration limits

Name	Product identifier	Specific concentration limits
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	CAS-No.: 84605-29-8 EC-No.: 283-392-8 REACH-no: 01-2119493626-26	( 15 ≤C ≤ 100) Skin Irrit. 2, H315 ( 15 ≤C < 20) Eye Irrit. 2, H319 ( 20 <C ≤ 100) Eye Dam. 1, H318

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3. Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center or a doctor if you feel unwell.

# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: After adequate first aid, no further treatment is required unless symptoms reappear. Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after ingestion	: After adequate first aid, no further treatment is required unless symptoms reappear.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable protective clothing and eye/face protection.
Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Store in a well-ventilated place. Keep cool.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.
- Storage temperature : 45 °C
- Storage area : Store away from heat. Store in a well-ventilated place.
- Special rules on packaging : Keep only in original container. Store in a closed container.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1. National occupational exposure and biological limit values

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m <sup>3</sup>

  

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

No additional information available

##### 8.1.5. Control banding

No additional information available

#### 8.2. Exposure controls

##### 8.2.1. Appropriate engineering controls

No additional information available

# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

No additional information available

#### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

#### 8.2.2.3. Respiratory protection

No additional information available

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

**Other information:**

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -33 °C
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: > 230 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 90.2 mm <sup>2</sup> /s @40°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 877.8 kg/m <sup>3</sup> @15°C
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Not established.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)</b>	
LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)</b>	
LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h
<b>Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)</b>	
LD50 oral (rat)	3100 mg/kg (OECD 401)
LD50 dermal (rat)	> 2002 mg/kg (OECD 402)
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 2.3 mg/l/4h (OECD 403)
ATE CLP (oral)	3100 mg/kg bodyweight

# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 4000 µg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 0.835 mg/l/4h

Skin corrosion/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-repeated exposure	: Not classified
Additional information	: Based on available data, the classification criteria are not met

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
NOAEL (oral, rat, 90 days)	160 mg/kg bodyweight

Aspiration hazard	: Not classified
Additional information	: Based on available data, the classification criteria are not met

79060 - Motor Oil Mineral Plus SN 15W-40	
Viscosity, kinematic	90.2 mm <sup>2</sup> /s @40°C

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

### 11.2.2. Other information

Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met
---	--

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata
<b>Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)</b>	
LC50 - Fish [1]	4.5 mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	23 mg/l Daphnia magna
EC50 72h - Algae [1]	24 mg/l Desmodesmus subspicatus
NOEC chronic crustacea	0.4 mg/l Daphnia magna
NOEC chronic algae	10 mg/l Desmodesmus subspicatus
<b>Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased</b>	
LC50 - Fish [1]	> 1000 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna
EC50 96h - Algae [1]	> 500 mg/l Pseudokirchneriella subcapitata
<b>12.2. Persistence and degradability</b>	
<b>79060 - Motor Oil Mineral Plus SN 15W-40</b>	
Persistence and degradability	Not established.
<b>Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F
<b>Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	1.5 % 28 Days (OECD 301 B)
<b>Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	13.4 % OECD 301B 28 days



# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

### 12.3. Bioaccumulative potential

#### 79060 - Motor Oil Mineral Plus SN 15W-40

Bioaccumulative potential	Not established.
---------------------------	------------------

#### Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

Partition coefficient n-octanol/water (Log Kow)	> 4
---	-----

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

Partition coefficient n-octanol/water (Log Pow)	9.2
---	-----

#### Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Partition coefficient n-octanol/water (Log Pow)	0.56
---	------

#### Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased

Partition coefficient n-octanol/water (Log Pow)	9.5
---	-----

### 12.4. Mobility in soil

#### Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

ADR	IMDG	IATA	ADN	RID
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Added	

# 79060 - Motor Oil Mineral Plus SN 15W-40

## Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-statements	
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

Safety Data Sheet (SDS), EU

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness