

Engine Oil Super SHPD 15W-40

Synthetic MID SAPS Heavy Duty Diesel Engine Oil

Engine Oil Super SHPD 15W-40 is a fuel saving MID SAPS super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particle Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system.

Product Code: 76260

Engine Oil Super SHPD 15W-40 is formulated with high refined synthetic base stock in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- · Extended drain intervals.
- Complies with strictest European emission regulation.

Engine Oil Super SHPD 15W-40 meets the following performance criteria:

Approved Volvo VDS 4.5 Mack EOS-4.5 Renault VI RLD-3

MB-Approval 228.31

Meets API CK-4 ACEA E6/E9 Cummins CES 20086

Deutz DQC IV-18-LA MAN M3775 CAT ECF-3

DDC93K222 MTU Type 3.1

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m ³	ASTM D4052	866
Kin. Viscosity @40°C	mm²/s	ASTM D7042	104
Kin. Viscosity @100°C	mm²/s	ASTM D7042	15
Viscosity Index		ASTM D2270	150
Viscosity CCS @-20°C	сР	ASTM D5293	3800
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.9
Sulphated Ash	%Wt	ASTM D874	1.00