

Gear Oil MP 80W-90

Automotive Multi Purpose Mineral Gear Oil

Gear Oil MP 80W-90 is an universal high performance mineral multi purpose gear oil for use in different applications, such as; manual transmission and transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture, where a SAE 80W-90 GL-5 oil is been required.

Product Code: 76340

Gear Oil MP 80W-90 is formulated with high refined mineral base stocks in combination with a special additive technology to achieve the following performance:

- Very good protection against wear.
- Very good performance against the forming of foam and corrosion.
- Good Oxidation- and thermal stability.

Gear Oil MP 80W-90 meets the following performance criteria:

API GL-5 MIL-L-2105D MAN 342 M1 MAN 342 M2 ZF TE-ML 05A, 7A, 08, 16B, 16C, 16D, 17B, 19B, 21A MB 235.0 Volvo 1273.10

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	80W-90
Density @15°C	kg/m³	ASTM D4052	883
Kin. Viscosity @40°C	mm²/s	ASTM D7042	123
Kin. Viscosity @100°C	mm²/s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	114
Viscosity Brookfield @-26°C	сР	ASTM D5293	90000
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36

 Date Issued: 05-03-2021
 Supersedes: 08-11-2018
 Revision Nr.: 03