



ATF Dexron III

Product Code: 76450

Automatic Transmission Fluid

ATF Dexron III is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger car, light vans and commercial vehicles.

ATF Dexron III is formulated on high refined solvent mineral and synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very high viscosity Index.
- Low pourpoint.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

ATF Dexron III meets the following performance criteria:

DEXRON IIIF/G/H	Allison C4	CAT TO-2	MAN 339 Z1/Z2
MAN 339 V1/V2	MB 236.10/236.9/236.7/236.5/236.1		Voith 55.6335
Mercon	Volvo 97341	ZF 02F/03D/04D	ZF 11A/11B/14B/16L

Typical Analysis

Properties	Unit	Method	Typical Value
Color			Red
Density @15°C	kg/m ³	ASTM D4052	847
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	35
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.5
Viscosity Index		ASTM D2270	186
Viscosity Brookfield @-40°, max.	cP	ASTM D2983	14000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-51

Date Issued: 08-03-2021	Supersedes: 09-11-2018	Revision Nr.: 03
-------------------------	------------------------	------------------