



## Hydraulic Oil HM 100

Product Code: 76550

Mineral hydraulic fluid

**Hydraulic Oil HM 100** is an universal mineral high grade EP oil for use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application.

**Hydraulic Oil HM 100** is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Excellent stability against oxidation.
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.

**Hydraulic Oil HM 100** exceeds the following performance criteria:

DIN 51524-2 HLP    ISO 11158 HM    ASTM D6158 HM    AFNOR NF E 48-603 HM  
Sauer Danfoss 520L0463

### Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	100
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	880
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	95
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	10.7
Viscosity Index		ASTM D2270	97
Flash Point COC	°C	ASTM D92	>205
Pour Point	°C	ASTM D7346	-24
Air Release Value @75°C	Minutes	ASTM D3427	Pass
Demulsibility @82°C	Minutes	ASTM D1401	Pass

Date Issued: 09-03-2022	Supersedes: 11-03-2021	Revision Nr.: 03
-------------------------	------------------------	------------------