



Hydraulic Oil HV 22

Product Code: 76580

Mineral hydraulic fluid

Hydraulic OIL HV 22 is an universal HVI mineral high grade EP oil for use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application.

Hydraulic OIL HV 22 is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Excellent stability against oxidation.
- High Viscosity Index
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.
- Very good thermal stability.

Hydraulic OIL HV 22 exceeds the following performance criteria:

DIN 51524-3 HVLP ISO 11158 HV ASTM D6158 HV AFNOR NF E 48-603 HV
Sauer Danfoss 520L0463

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	22
Density @15°C	kg/m ³	ASTM D4052	849
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	23
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	5.5
Viscosity Index		ASTM D2270	190
Flash Point COC	°C	ASTM D92	>175
Pour Point	°C	ASTM D7346	-48
Air Release Value @50°C	Minutes	ASTM D3427	Pass
Demulsibility @54°C	Minutes	ASTM D1401	Pass

Date Issued: 09-03-2022	Supersedes: 15-03-2021	Revision Nr.: 03
-------------------------	------------------------	------------------