



4-Stroke Motorcycle Oil Semi Synth 15W-50 Product Code: 76780
 Synthetic technology engine oil for motorcycles

4-Stroke Motorcycle Oil Semi Synthetic 15W-50 is a high performance semi synthetic engine oil specially designed for use in 4-stroke motorcycles with work under severe operation conditions and is can be used in gearbox and wet clutches.

4-Stroke Motorcycle Oil Semi Synthetic 15W-50 is based on high quality synthetic technology Hydrocracked and hydro treated base stocks in combination with a special selected additive package to obtain the following properties.

- Very good thermal- and oxidation stability.
- Excellent anti-wear, anticorrosion and antifoam properties.
- High friction properties to eliminate clutch slippage.
- Low temperature to ensure an easy cold start.

4-Stroke Motorcycle Oil Semi Synthetic 15W-50 meets the following performance criteria:

API SN

JASO MA2

Typical Analysis

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-50
Density @15°C	kg/m ³	ASTM D4052	858
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	118
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	17.4
Viscosity Index		ASTM D2270	162
CCS Viscosity -20°C	cP	ASTM D5293	3500
Flashpoint COC	°C	ASTM D92	>201
Pourpoint	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.6

Date Issued: 03-08-2022	Supersedes: 08-04-2021	Revision Nr.: 04
-------------------------	------------------------	------------------