



## 4-Stroke Motorcycle Oil Synthetic 20W-50

Product Code: 76790

Full Synthetic Oil for 4-stroke motorcycles.

**4-Stroke Motorcycle Oil Synthetic 20W-50** is a high performance full synthetic engine oil specially designed for use in 4-stroke motorcycles with work under severe operation conditions and is can be used in gearbox and wet clutches.

**4-Stroke Motorcycle Oil Synthetic 20W-50** is based on high quality full synthetics (PAO) base stocks in combination with a special selected additive package to obtain the following properties.

- Extreme good thermal- and oxidation stability.
- Excellent anti-wear, anticorrosion and antifoam properties.
- High friction properties to eliminate clutch slippage.
- Low temperature to ensure an easy cold start.

**4-Stroke Motorcycle Oil Synthetic 20W-50** exceeds the following performance criteria:

API SN

JASO MA-2

### Typical Analysis

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J300	20W-50
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	879
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	140.6
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	21.0
Viscosity Index		ASTM D2270	175
Viscosity -15°C	cP	ASTM D5293	<9500
Flashpoint COC	°C	ASTM D92	>201
Pourpoint	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.6
Sulphated Ash	% Wt	ASTM D874	1.16

Date Issued: 13-4-2021

Supersedes: 30-06-2015

Revision Nr.: 02