

2-Stroke Snowmobile Synth

Fully synthetic 2-stroke snowmobile oil

2-Stroke Snowmobile Synth is a high performance low smoke 2-stroke snowmobile oil based on 100% synthetic technology to be used in 2-stroke snowmobiles and other gasoline engines.

2-Stroke Snowmobile Synth is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties.

- Excellent engine protection on cleanliness.
- Low smoke even under extreme operation conditions.
- High thermal and oxidation stability.
- Exceptional protection against piston scuffing.
- High antiwear and anticorrosion properties.
- Homogeneous mixture even at low ambient temperatures.

2-Stroke Snowmobile Synth exceeds the following performance criteria;

JASO FD ROTAX 253 ISO-L-EGD

API TC

ISO 6743-15

Product Code: 76830

Typical Analysis

Properties	Unit	Method	Typical Value
Density @15°C	kg/m ³	ASTM D4052	874
Kin. Viscosity @40°C	mm²/s	ASTM D7042	49.06
Kin. Viscosity @100°C	mm²/s	ASTM D7042	8.9
Viscosity Index		ASTM D2270	164
Flash Point COC	°C	ASTM D92	92
Pour Point	°C	ASTM D7346	-51
Total Base Number	mgKOH/g	ASTM D2896	1.6
Sulphated Ash	%Wt	ASTM D874	0.15