

Industrial Gear Oil 68

Mineral Industrial Gear Oil

Industrial Gear Oil 68 is a high performance extreme pressure gear oils developed for lubrication of heavy duty industrial gears working under severe operating conditions.

Product Code: 77050

Industrial Gear Oil 68 is based on high quality mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- High thermo-oxidative stability helps resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.
- Excellent demulsibility property enables trouble-free operation in conditions encountering water/ moisture.

Industrial Gear Oil 68 exceeds the following performance criteria:

DIN 51517-3 CLP ISO 12925-1 CKD AGMA 9005 E-02 US Steel 224 David Brown S1.53.101

Typical Analysis

| Properties | Unit | Method | Typical Value |
|-----------------------|-------------------|-------------|---------------|
| | | | |
| ISO VG Grade | | ISO 3448 | 68 |
| Density @15°C | kg/m ³ | ASTM D4052 | 879 |
| Kin. Viscosity @40°C | mm²/s | ASTM D7042 | 64.5 |
| Kin. Viscosity @100°C | mm²/s | ASTM D7042 | 8.4 |
| Viscosity Index | | ASTM D2270 | 100 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -18 |
| FZG Fail Load Stage | | DIN 51354-2 | >12 |
| Total Acid Number | mgKOH/g | ASTM D664 | 0.6 |

Date Issued: 16-04-2021 | Supersedes: 12-10-2015 | Revision Nr.: 02