



## Slideway CGLP 68

Product Code: 77150

Mineral Slide Way Oil

**Slideway CGLP 68** is a universal high performance machine tool lubricant specially designed for the lubrication of tableway.

**Slideway CGLP 68** meets also the requirements of gear boxes, spindles and hydraulic systems of different machine tools.

**Slideway CGLP 68** is based on high quality mineral virgin base oil in combination with a special additive to ensure the following properties.

- Excellent stick-slip properties.
- Very good antiwear, antirust and antifoam properties.
- High oxidation stability.
- Good resistance to high pressure and loads.
- Excellent demulsification properties.
- Good filterability.
- Strong adhesion to (vertical) slides

**Slideway CGLP 68** meets the following performance limits;

DIN 51517 part III	DIN 51524 part II	ISO 11158 HG	ISO 19378 GA & GB
AGMA 9005 E02 (EP)	General Motors LS2	AIST 224	FZG 12

### Typical Analysis

Property	Unit	Method	Typical Value
ISO VG Grade			68
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	878
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	67.9
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	8.8
Viscosity Index		ASTM D2270	101
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-24
FZG Fail Load Stage		DIN 51354-2	>12
Total Acid Number	mgKOH/g	ASTM D974	0.6

Date Issued: 22-04-2021	Supersedes: 03-04-2018	Revision Nr.: 02
-------------------------	------------------------	------------------