



Heat Transfer Oil 32

Product Code: 77400

Mineral heat transfer fluid

Heat Transfer Oil 32 is a premium quality heat transfer oil intended for use in closed indirect heating systems with expansion tanks temperatures up to 315°C and for open heating systems provided that the oil temperature does not exceed 180°C

Heat Transfer Oil 32 is based on high quality mineral base oil to ensure the following properties:

- Excellent thermal and oxidation stability.
- Minimizes deposit formation and viscosity increase.
- Extended service life and reduced downtime.
- Exceptional resistance to thermal cracking and decomposition enables this oil to perform well up to a maximum bulk oil temperature of 315°C with minimal interference with heat transfer capability.
- High specific heat and thermal conductivity of this oil provides more rapid heat dissipation.
- Superior low temperature fluidity ensures quick circulation at start-up and reduced risk of local over-heating.
- Non corrosive to aluminum, steel, copper, brass or bronze.
- Non-toxicity of this oil provides easy disposal of used oil.

Typical Properties:

Properties	Unit	Method	Typical Value
ISO VG Class			32
Density@15°C	kg/m ³	ASTM D4052	870
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	31.1
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	5.3
Viscosity Index		ASTM D2270	100
Flash Point COC	°C	ASTM D92	220
Pour Point	°C	ASTM D7346	-15

Date Issued: 26-04-2021	Supersedes: 15-04-2015	Revision Nr.: 01
-------------------------	------------------------	------------------