



## Synthetic Heat Transfer Oil 25

Product Code: 77690

Synthetic heat transfer fluid

**Synthetic Heat Transfer Oil 25** is a high quality synthetic heat transfer oil intended for use in closed indirect heating systems with expansion tanks temperatures up to 350°C.

**Synthetic Heat Transfer Oil 25** is based on high quality synthetic base oil to ensure the following properties:

- Excellent thermal and oxidation stability.
- Minimizes deposit formation and viscosity increase.
- Extended service life and reduced downtime.
- Exceptional resistance to thermal cracking and decomposition enables this oil to perform well up to a maximum bulk oil temperature of 350°C with minimal interference with heat transfer capability.
- High specific heat and thermal conductivity of this oil provides more rapid heat dissipation.
- Superior low temperature fluidity ensures quick circulation at start-up and reduced risk of local over-heating.
- Non corrosive to aluminum, steel, copper, brass or bronze.
- Non-toxicity of this oil provides easy disposal of used oil.

### Typical Properties:

Properties	Unit	Method	Typical Value
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	838
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	23.4
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	4.9
Viscosity Index		ASTM D2270	133
Flash Point COC	°C	ASTM D92	230
Pour Point	°C	ASTM D7346	-21

Date Issued: 26-04-2021

Supersedes: 16-05-2013

Revision Nr.: 01