



Gas Engine Oil LA 30

Product Code: 77780

High Performance Heavy Duty Gas Engine Oil

Gas Engine Oil LA 30 is a Low Ash high performance Heavy Duty Gas Engine Oil specially designed for use in stationary gas engines which run on natural and/or biogas and operate under severe conditions in high temperatures.

Gas Engine Oil LA 30 is based on a high quality hydro processed base oils in combination with a special selected additive package to obtain the following properties:

- Excellent thermal-, nitration-, and oxidation stability.
- Reducing of combustion chamber deposits.
- Minimize ring scuffing.
- Protect against corrosive wear.
- Improving engine performance.

Gas Engine Oil LA 30 exceeds the following performance criteria:

API CF; Waukesha Cogeneration; Dresser Rand Category III, Jenbacher

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	30
Density @15°C	kg/m ³	ASTM D4052	880
Kin. Viscosity @40°C	mm ² /s	ASTM D445	96
Kin. Viscosity @100°C	mm ² /s	ASTM D445	11.3
Viscosity Index		ASTM D2270	95
Flash Point COC	°C	ASTM D92	>215
Pour Point	°C	ASTM D7346	-15
Total Base Number	mgKOH/g	ASTM D2896	5.6
Sulphated Ash	%Wt	ASTM D874	0.49

Date Issued: 21-04-2021	Supersedes: 27-10-2015	Revision Nr.: 02
-------------------------	------------------------	------------------