



## Engine Oil Super SHPD 10W-40

Product Code: 78260

Synthetic MID SAPS Heavy Duty Diesel Engine Oil

**Engine Oil Super SHPD 10W-40** is a fuel saving MID SAPS super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particle Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system.

**Engine Oil Super SHPD 10W-40** is formulated with high refined synthetic technology base stock in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals.
- Complies with strictest European emission regulation.

**Engine Oil Super SHPD 10W-40** exceeds the following performance criteria:

<b>Approved</b>	Volvo VDS 4.5	Mack EOS-4.5	Renault VI RLD-3
<b>Exceeds</b>	API CK-4 MB 228.51 MAN M3775 MTU Type 3.1	ACEA E6/E9 Cummins CES 20086 DDC93K222 IVECO	MB 228.31 Deutz DQC IV-18 LA CAT ECF-3 DAF

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	862
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	98
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	14.6
Viscosity Index		ASTM D2270	154
Viscosity CCS @-25°C	cP	ASTM D5293	5850
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	10.1
Sulphated Ash	%Wt	ASTM D874	0.96

Date Issued: 04-04-2022	Supersedes: 14-04-2021	Revision Nr.: 08
-------------------------	------------------------	------------------