



## Gear Oil MTF 75W-80

Product Code: 78410

Manual Transmission Oil

**Gear Oil MTF 75W-80** is a high quality manual transmission fluid designed for passenger- and light commercial vehicles using both manual transmissions and transaxles. Not suitable for differentials and other API: GL-5 applications

**Gear Oil MTF 75W-80** is based on high quality synthetic technology base oil in combination with a special additive package to ensure the following properties:

- Exceptional thermo-oxidative stability.
- Superior lubricating properties provide improved fuel economy.
- Exceptional load bearing characteristics.
- Effective rust and corrosion protection.
- Outstanding low temperature fluidity provides smoother shifting at low ambient temperatures.
- Good gear engagement with a variety of synchronizer materials including brass, carbon, sintered bronze and molybdenum

**Gear Oil MTF 75W-80** is recommended for the following specifications:

API: GL-4	BMW MTF LT-2 / LT-3 / LT-4	Ford WSD-M2C200-C
GM 1940182	GM 1940764	GM 1940768
GM 1940004	GM 19259104	Nissan MT-XZ
MB 235.10	PSA B71 2330	MTF94
Honda MTF II / III	Volvo 97308	Volvo 97309
VW G 052 171	VW G 052 178	VW G 052 512
VW G 052 527	VW G 070 726	VW G 060 726
Renault (NFJ/NFP/TRJ/TRT/TRZ)		Ford WSS-M2C200-D2
		Nissan MT-XZ TL
		Honda MTF
		VW G 009 317
		VW G 052 726
		VW G50

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	75W-80
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	863
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	52
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	9.4
Viscosity Index		ASTM D2270	165
Brookfield Viscosity @-40°C	cP	ASTM D2983	86000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-42

Date Issued: 09-03-2021	Supersedes: 31-03-2017	Revision Nr.: 02
-------------------------	------------------------	------------------