



## ATF CVT Plus

Automatic Transmission Fluid

Product Code: 78420

**ATF CVT Plus** is a fully synthetic ultra-high performance CVT fluid formulated with selected base stocks and specially developed for use in the latest generation of Continuously Variable Transmission (CVT) – gearboxes which transfer traction via steel-made traction chain or push-belts.

**ATF CVT Plus** is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Good thermo-and oxidation.
- Extended drain interval possible.
- Excellent antiwear, antirust and anticorrosion technology.
- High Viscosity index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Enhanced Low temperature fluidity assist in good cold start performance.
- Compatibility with all common seal materials

**ATF CVT Plus** exceeds the following performance criteria:

Toyota CVTF TC	Toyota CVTF FE	Nissan NS-1	Nissan NS-2
Nissan NS-3	Honda HMMF	Honda HCF2	Mitsubishi SP-III
Mitsubishi CVTF-J1	Subaru ECVT	Subaru iCVT	Daihatsu Ammix CVT
Suzuki CVTF Green 1	Hyundai SP-III	EZL 799	Chrysler/Jeep NS-2
Ford WSS-M2C928	MB 236.20		

### Typical Analysis

Properties	Unit	Method	Typical Value
Color			Amber
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	845
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	34
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	7,3
Viscosity Index		ASTM D2270	187
Brookfield Viscosity @-40°C	cP	ASTM D2983	16000
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-48

Date Issued: 09-03-2021	Supersedes: 21-7-2015	Revision Nr.: 01
-------------------------	-----------------------	------------------