

## **Outboard Engine Oil 10W-40**

4-stroke Outboard & Sterndrive Engine oil

**Outboard Engine Oil 10W-40** is a premium 4-stroke engine oil specially designed for the most modern high output gasoline power, water cooled outboard / inboard and personal watercraft engines. It is specially developed to exceed the performance requirements of National Marine Manufacturers Association's specification NMMA FC-W Catalyst Compatible® (Four Cycle-Water specification).

Product Code: 78820

**Outboard Engine Oil 10W-40** is based on a high quality hydro processed base oils in combination with a special selected additive package to obtain the following properties:

- Exceptional shear stability.
- Advanced rust inhibitors guard against rust & corrosion even in marine salt water environment.
- Good Low temperature fluidity assists easy cold start.
- Active cleaning agents provide superior engine cleanliness

**Outboard Engine Oil 10W-40** exceeds the following performance criteria:

NMMA FC-W Catalyst Compatible API SM

## **Typical Analysis**

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15°C	kg/m³	ASTM D4052	852
Kin. Viscosity @40°C	mm²/s	ASTM D7042	85
Kin. Viscosity @100°C	mm²/s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	161
Viscosity CCS -25°C	сР	ASTM D5293	4400
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	7.3
Sulphated Ash	%Wt	ASTM D874	0.8

Date Issued: 13-04-2021 Supersedes: 11-07-2018 Revision Nr.: 02