



Hydraulic Oil HV ZF 22

HVI Zinc Free mineral hydraulic fluid

Product Code: 78920

Hydraulic Oil HV ZF 22 is an universal Zinc free mineral oil with a High Viscosity Index (HVI) for the use in heavy duty hydraulic systems and light duty gearboxes, bearings and general lubrication. Not suitable for turbine application.

Hydraulic Oil HV ZF 22 is formulated with high quality refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Excellent stability against oxidation.
- High Viscosity Index.
- Very good protection against wear.
- Good water demulsibility.
- Very good foaming properties.
- Very effective to rust and corrosion.
- Very good thermal stability.
- Avoid reactions with metals like Silver.

Hydraulic Oil HV ZF 22 meets the following performance criteria:

DIN 51524/3 HVL P GM LS-2 ISO 11158 HV Eaton Vickers M-2950-S
Eaton Vickers I-286-S Denison HF-0 Bosch Rexroth RE 90 220

Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	22
Density @15°C	kg/m ³	ASTM D4052	842
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	20
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	5.4
Viscosity Index		ASTM D2270	194
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-48
FZG Fail Load Stage		DIN 51534-2	11
Air Release Value @50°C	Minutes	ASTM D3427	Pass
Demulsibility @54°C	Minutes	ASTM D1401	Pass

Date Issued: 23-03-2021	Supersedes: 16-02-2018	Revision Nr.: 01
-------------------------	------------------------	------------------