



## 4-Stroke Motorcycle Oil Syn 10W-60

Product Code:79700

Fully Synthetic Motorcycle Oil

**4-Stroke Motorcycle Oil 10W-60** is a ultra-high performance 4-stroke gasoline engine oil developed specifically to meet the special requirements of latest high performance air and water-cooled 4-stroke motorcycles, even with catalytic converters. It provides excellent protection to engine, gearbox and wet clutch used in 4-stroke motorcycles and ensures highest degree of reliability even under severe operating conditions and temperatures.

**4-Stroke Motorcycle Oil 10W-60** is based on a mixture of synthetic PolyAlphaOlefin (PAO) base stock in combination with ester and a special selected additive package to obtain the following properties:

- Outstanding thermo-oxidative stability.
- Exceptional antiwear, antirust and anticorrosion properties.
- Controlled frictional properties eliminate clutch slippage.
- Increased power/ fuel economy and improves drivability.
- Excellent dispersancy and detergency properties.
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection.
- Outstanding low temperature properties enable easy starting at low ambient temperatures and ensure effective lubrication and wear protection at start up.
- Low volatility characteristics reduce oil consumption and hydrocarbon pollution.

**4-Stroke Motor Cycle Oil 10W-60** exceeds the following performance criteria:

JASO MA / MA2

API SN

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-60
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	851
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	175
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	25.5
Viscosity Index		ASTM D2270	180
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	8.6

Date Issued: 14-04-2021	Supersedes: 13-03-2018	Revision Nr.: 01
-------------------------	------------------------	------------------