



## Engine Oil HD 15W-40

Product Code: 79900

Mineral Heavy Duty Diesel Engine Oil

**Engine Oil HD 15W-40** is a high performance universal mineral engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year and is formulated for use in Euro I, Euro II, Euro III, Euro IV and Euro V engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with particulate filters.

**Engine Oil HD 15W-40** is formulated on high refined solvent mineral base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Not suitable for engine equipped with a Diesel Particulate Filter (DPF).

**Engine Oil HD 15W-40** meets the following performance criteria:

API CG-4  
MAN M271

API SH  
MTU type 1

ACEA E2  
Volvo VDS

MB 228.1  
Renault RD

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	877
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	106
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	14.3
Viscosity Index		ASTM D2270	137
Viscosity CCS @-20°C	cP	ASTM D5293	5900
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.5

Date Issued: 04-03-2021	Supersedes: 30-08-2018	Revision Nr.: 01
-------------------------	------------------------	------------------