



76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878
Issue date: 10/07/2012 Revision date: 03/07/2019 Supersedes version of: 02/12/2015 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50
Product code : 76780
Type of product : Lubricant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Transnational Blenders B.V.
Wieldrechtseweg 37
3316 BG Dordrecht - Netherlands
T +31 (0)78 6527652
technical@tnb.nl - www.tnb.nl

1.4. Emergency telephone number

Emergency number : +31 (0)78 6527652
Monday to Friday: 09:00 - 16:00 (CET)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU > 2015: According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

2.3. Other hazards

Other hazards which do not result in classification : Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	50 – 75	Not classified
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil substance with a Community workplace exposure limit (Note L)	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	10 – 25	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated light paraffinic; Baseoil (Note L)	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	2.5 – 10	Asp. Tox. 1, H304
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	CAS-No.: 84605-29-8 EC-No.: 283-392-8 REACH-no: 01-2119493626-26	0.5 – 2.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411
Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased	EC-No.: 701-251-5 REACH-no: 01-2119524004-56	0.5 – 2.5	Aquatic Chronic 4, H413

Specific concentration limits

Name	Product identifier	Specific concentration limits
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	CAS-No.: 84605-29-8 EC-No.: 283-392-8 REACH-no: 01-2119493626-26	(15 ≤C ≤ 100) Skin Irrit. 2, H315 (15 ≤C < 20) Eye Irrit. 2, H319 (20 <C ≤ 100) Eye Dam. 1, H318

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after ingestion	: After adequate first aid, no further treatment is required unless symptoms reappear.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Eliminate all ignition sources if safe to do so.
Emergency procedures	: Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	--

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool.
Storage temperature	: 50 °C

76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Storage area : Store in a well-ventilated place. Store away from heat.
Special rules on packaging : Store in a closed container. Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	5 mg/m ³
IOEL STEL	10 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

No additional information available

8.2.2.2. Skin protection

No additional information available

8.2.2.3. Respiratory protection

No additional information available

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Brown.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -24 °C
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: 210 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 134.4 mm ² /s @40°C
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 874 kg/m ³ @15°C
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rabbit)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

LD50 oral (rat)	3100 mg/kg (OECD 401)
LD50 dermal (rat)	> 2002 mg/kg (OECD 402)
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 2.3 mg/l/4h (OECD 403)
ATE CLP (oral)	3100 mg/kg bodyweight

Phenol, dodecyl-, sulfurized, carbonates, calcium salts, overbased

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 4000 µg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 0.835 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
----------------------------	---

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
----------------------------	----------------------

76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight
Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
NOAEL (oral, rat, 90 days)	160 mg/kg bodyweight
Aspiration hazard	: Not classified
76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50	
Viscosity, kinematic	134.4 mm ² /s @40°C

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata
Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata

76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
LC50 - Fish [1]	4.5 mg/l Oncorhynchus mykiss
EC50 - Crustacea [1]	23 mg/l Daphnia magna
EC50 72h - Algae [1]	24 mg/l Desmodesmus subspicatus
NOEC chronic crustacea	0.4 mg/l Daphnia magna
NOEC chronic algae	10 mg/l Desmodesmus subspicatus

Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased	
LC50 - Fish [1]	> 1000 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna
EC50 96h - Algae [1]	> 500 mg/l Pseudokirchneriella subcapitata

12.2. Persistence and degradability

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)	
Biodegradation	31 % 28 d, OECD TG 301 F

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	1.5 % 28 Days (OECD 301 B)

Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased	
Persistence and degradability	Not readily biodegradable.
Biodegradation	13.4 % OECD 301B 28 days

12.3. Bioaccumulative potential

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil (64742-54-7)	
Partition coefficient n-octanol/water (Log Kow)	> 4

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil (64742-65-0)	
Bioconcentration factor (BCF REACH)	260
Partition coefficient n-octanol/water (Log Pow)	9.2

Distillates (petroleum), hydrotreated light paraffinic; Baseoil (64742-55-8)	
Partition coefficient n-octanol/water (Log Pow)	> 6

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
Partition coefficient n-octanol/water (Log Pow)	0.56

Phenol, dodecyl-, sulfurized, carbonates,calcium salts, overbased	
Partition coefficient n-octanol/water (Log Pow)	9.5

76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

12.4. Mobility in soil

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations :

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information available				

14.6. Special precautions for user

Overland transport

No data available

Transport by sea

No data available

Air transport

No data available

76780 - 4-Stroke Motorcycle Oil Semi Synth 15W-50

Safety Data Sheet

SDS EU format according to COMMISSION REGULATION (EU) 2020/878

Inland waterway transport

No data available

Rail transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
EUH210	Safety data sheet available on request.

Safety Data Sheet (SDS), EU

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness