



# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 18/12/2020 Revision date: 29/09/2022 Supersedes version of: 18/12/2020 Version: 1.1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : 79200 - Engine Oil Special Synthetic UHPD 10W-40  
Product code : 79200  
Type of product : Lubricant

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Consumer use, Professional use  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Transnational Blenders B.V. B.V.  
Wieldrechtseweg, 37  
NL- 3316 BG Dordrecht – Netherlands Zuid Holland  
Netherlands  
T +31 (0)78 6527652  
[technical@tnb.nl](mailto:technical@tnb.nl) - [www.tnb.nl](http://www.tnb.nl)

#### 1.4. Emergency telephone number

Emergency number : +31 (0)78 6527652  
Monday to Friday: 09:00 - 16:00 (CET)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

#### 2.3. Other hazards

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil substance with a Community workplace exposure limit	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889-13	35 – 50	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	25 – 50	Not classified
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based substance with national workplace exposure limit(s) (BE, BG, CZ, DK, ES, FI, GR, HU, IE, LT, LV, NL, PL, PT, SE, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 72623-86-0 EC-No.: 276-737-9 EC Index-No.: 649-482-00-X REACH-no: 01-2119474878-16	3 – 10	Asp. Tox. 1, H304
reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	CAS-No.: 125643-61-0 EC-No.: 406-040-9 EC Index-No.: 607-530-00-7 REACH-no: 01-0000015551-76	1 – 5	Aquatic Chronic 4, H413
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	0.1 – 3	Asp. Tox. 1, H304
Distillates (petroleum), solvent-dewaxed light paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, ES, FI, GR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64742-56-9 EC-No.: 265-159-2 EC Index-No.: 649-469-00-9 REACH-no: 01-2119480132-48	0.1 – 3	Not classified
Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil	CAS-No.: 64742-70-7 EC-No.: 265-174-4 EC Index-No.: 649-477-00-2 REACH-no: 01-2119487080-42	0.1 – 3	Asp. Tox. 1, H304
Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate	CAS-No.: 93819-94-4 EC-No.: 298-577-9 REACH-no: 01-2119543726-33	0.3 – 3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate)	CAS-No.: 93819-94-4 EC-No.: 298-577-9 REACH-no: 01-2119543726-33	( 6.25 ≤C < 100) Skin Irrit. 2, H315 ( 10 ≤C < 12.5) Eye Irrit. 2, H319 ( 12.5 ≤C < 100) Eye Dam. 1, H318

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area.
----------------------	----------------------------

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
Handling temperature	: < 45 °C
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool.
Storage temperature	: < 45 °C

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	5 mg/m <sup>3</sup>
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
<b>Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	5 mg/m <sup>3</sup>
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>
<b>United Kingdom - Occupational Exposure Limits</b>	
WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup>

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

#### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup> ACGIH TLV (inhalable fraction)
----------	--

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

##### Eye protection:

Use splash goggles when eye contact due to splashing is possible. Safety glasses

#### Eye protection

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

##### 8.2.2.2. Skin protection

##### Skin and body protection:

Avoid prolonged and repeated contact with skin

##### Hand protection:

Protective gloves

#### Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR), Neoprene rubber (HNBR)	5 (> 240 minutes)	0.7	3 (> 0.65)	EN ISO 374
	Polyvinylchloride (PVC)	2 (> 30 minutes)	0.4	3 (> 0.65)	EN ISO 374

##### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

##### 8.2.2.4. Thermal hazards

No additional information available

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Brown.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -36 °C ASTM D7346
Boiling point	: Not available
Flammability	: Non flammable.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 201 °C ASTM D92
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 95 mm <sup>2</sup> /s @40°C (ASTM D7042)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 860 kg/m <sup>3</sup> @ 15°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 2000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

LD50 oral (rat)	> 2000 mg/kg OECD Test Guideline 401
LD50 dermal (rat)	> 2000 mg/kg OECD Test Guideline 402

#### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

LD50 oral (rat)	2600 mg/kg bw/day Tested according to Annex V of Directive 67/548/EEC
LD50 dermal (rabbit)	> 3160 mg/kg bodyweight OECD Test Guideline 402
LC50 inhalation (rat) (mg/l)	> 2 mg/l (1h) - OECD403

#### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

LD50 oral (rat)	> 5000 mg/kg bodyweight
LD50 dermal (rat)	> 5000 mg/kg
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 2.18 mg/l/4h

#### Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	5 mg/l/4h

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408
----------------------------	---

### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
----------------------------	----------------------

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
----------------------------	----------------------

NOAEL (dermal, rat/rabbit, 90 days)	≈ 1000 mg/kg bodyweight
-------------------------------------	-------------------------

### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

NOAEL (oral, rat, 90 days)	160 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	---

### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
----------------------------	---

Aspiration hazard	: Not classified
-------------------	------------------

### 79200 - Engine Oil Special Synthetic UHPD 10W-40

Viscosity, kinematic	95 mm <sup>2</sup> /s @40°C (ASTM D7042)
----------------------	--

### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Viscosity, kinematic	109 mm <sup>2</sup> /s @40°C
----------------------	------------------------------

### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Viscosity, kinematic	1.99 – 847 mm <sup>2</sup> /s 40°C
----------------------	------------------------------------

### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)

Viscosity, kinematic	47 mm <sup>2</sup> /s
----------------------	-----------------------

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Viscosity, kinematic	150 (1.99 – 847) mm <sup>2</sup> /s @40°C
----------------------	---

### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

Viscosity, kinematic	3050 mm <sup>2</sup> /s @40°C
----------------------	-------------------------------

### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Viscosity, kinematic	1.99 – 847 mm <sup>2</sup> /s Temp.: '40°C
----------------------	--

### Paraffin oils (petroleum), catalytic dewaxed heavy; Baseoil (64742-70-7)

Viscosity, kinematic	19 mm <sup>2</sup> /s @40°C
----------------------	-----------------------------

## 11.2. Information on other hazards

No additional information available

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified
Not rapidly degradable	

<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Scenedesmus quadricauda
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata (72h)
<b>Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)</b>	
LC50 - Fish [1]	> 100 mg/l
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)
<b>reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)</b>	
LC50 - Fish [1]	> 74 mg/l Dania rerio (zebra fish) OECD Test Guideline 203
EC50 - Crustacea [1]	> 100 mg/l Daphnia magna (24h) OECD Test Guideline 202
EC50 72h - Algae [1]	> 3 mg/l Desmodesmus subspicatus (green algae) OECD Test Guideline 201
<b>Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)</b>	
LC50 - Fish [1]	4.5 mg/l Oncorhynchus mykiss (Rainbow trout)
EC50 - Crustacea [1]	5.4 mg/l Daphnia magna (water flea) OECD Test Guideline 202
EC50 96h - Algae [1]	2.1 mg/l Selenastrum capricornutum (green algae) OECD Test Guideline 201
ErC50 algae	2.1 mg/l Selenastrum capricornutum
<b>Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

NOEC chronic fish	≥ 1000 mg/l Oncorhynchus mykiss
NOEC chronic crustacea	10 mg/l Daphnia magna
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata

### 12.2. Persistence and degradability

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

#### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % 28 d OECD 301F

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Biodegradation	31 % 28 d OECD 301F
----------------	---------------------

#### reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Persistence and degradability	Not biodegradable.
Biodegradation	2 – 4 % OECD 301B

#### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

Persistence and degradability	Not readily biodegradable.
Biodegradation	1.5 % 28d - OECD 301 B

#### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % OECD 301F

### 12.3. Bioaccumulative potential

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow)	> 3.5
---	-------

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Bioconcentration factor (BCF REACH)	260
Partition coefficient n-octanol/water (Log Pow)	> 6

#### reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Bioconcentration factor (BCF REACH)	260 35 D, Oncorhynchus mykiss (Rainbow trout)
Partition coefficient n-octanol/water (Log Pow)	9.2

#### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

Partition coefficient n-octanol/water (Log Pow)	0.9 @23°C
---	-----------

### 12.4. Mobility in soil

#### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (72623-86-0)

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate (125643-61-0)

Ecology - soil Adsorbs into the soil.

### Zinc bis{O-(6-methylheptyl)} bis {O(sec-butyl)} bis dithiophosphate (93819-94-4)

Ecology - soil Adsorbs into the soil.

### Distillates (petroleum), solvent-dewaxed light paraffinic (64742-56-9)

Ecology - soil Adsorbs into the soil.

## 12.5. Results of PBT and vPvB assessment

No additional information available

## 12.6. Endocrine disrupting properties

No additional information available

## 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
HP Code : HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### Air transport

Not applicable

### Inland waterway transport

Not applicable

### Rail transport

Not applicable

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

##### REACH Annex XVII (Restriction List)

Contains no REACH substances with Annex XVII restrictions

##### REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

##### REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

##### PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

##### POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

##### Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

##### Explosives Precursors Regulation (2019/1148)

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

##### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes	Modified	
	Revision date	Modified	

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
	Flammability (solid, gas)	Added	
2.1	Adverse physicochemical, human health and environmental effects	Added	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures after inhalation	Added	
4.1	First-aid measures after eye contact	Added	
4.1	First-aid measures after ingestion	Added	
4.1	First-aid measures after skin contact	Added	
4.3	Other medical advice or treatment	Added	
5.1	Suitable extinguishing media	Added	
5.2	Hazardous decomposition products in case of fire	Added	
5.3	Protection during firefighting	Added	
6.1	Protective equipment	Added	
6.1	Emergency procedures	Added	
6.2	Environmental precautions	Added	
6.3	Methods for cleaning up	Added	
6.3	Other information	Added	
6.4	Reference to other sections (8, 13)	Added	
7.1	Precautions for safe handling	Added	
7.1	Hygiene measures	Added	
7.2	Storage conditions	Added	
8.2	Environmental exposure controls	Added	
8.2	Skin and body protection	Modified	
8.2	Appropriate engineering controls	Added	
8.2	Respiratory protection	Added	
8.2	Hand protection	Added	
8.2	Eye protection	Added	
9.1	Viscosity, kinematic	Modified	
9.1	Freezing point	Modified	
9.1	Flash point	Modified	
9.1	Density	Modified	
10.1	Reactivity	Added	
10.2	Chemical stability	Added	
10.3	Possibility of hazardous reactions	Added	
10.4	Conditions to avoid	Added	
10.6	Hazardous decomposition products	Added	
12.1	Ecology - general	Added	
13.1	Waste treatment methods	Added	

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes			
Section	Changed item	Change	Comments
13.1	HP Code	Added	
15.2	Chemical safety assessment	Added	
16	Abbreviations and acronyms	Added	

Abbreviations and acronyms:	
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
WGK	Water Hazard Class
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit

# 79200 - Engine Oil Special Synthetic UHPD 10W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Skin Irrit. 2	Skin corrosion/irritation, Category 2

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.