



2-Stroke Motorcycle Oil Synth

Product Code:76800

Fully synthetic 2-stroke motorcycle oil

2-Stroke Motorcycle Oil Synth is a high performance low smoke 2-stroke motorcycle oil based on 100% synthetic technology to be used in 2-stroke motorcycle, scooter, snow mobiles and other variety gasoline engines.

2-Stroke Motorcycle Oil Synth can **not** be used in 2-stroke outboard engines.

2-Stroke Motorcycle Oil Synth is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties.

- Excellent engine protection on cleanliness.
- Low smoke even under extreme operation conditions.
- High thermal and oxidation stability.
- Exceptional protection against piston scuffing.
- High antiwear and anticorrosion properties.
- Homogeneous mixture even at low ambient temperatures.

2-Stroke Motorcycle Oil Synth exceeds the following performance criteria;

JASO FD
Rotax 253

ISO-L-EGD
Husqvarna 346/372

API TC

ISO 6743-15

Typical Analysis

Properties	Unit	Method	Typical Value
Density @15°C	kg/m ³	ASTM D4052	874
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	49.3
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.0
Viscosity Index		ASTM D2270	165
Flash Point COC	°C	ASTM D92	108
Pour Point	°C	ASTM D7346	-51
Total Base Number	mgKOH/g	ASTM D2896	1.6
Sulphated Ash	%Wt	ASTM D874	0.15

Date Issued: 06-07-2023	Supersedes: 13-04-2021	Revision Nr.: 04
-------------------------	------------------------	------------------