

Engine Oil Super SHPD 10W-40

Synthetic MID SAPS Heavy Duty Diesel Engine Oil

Engine Oil Super SHPD 10W-40 is a fuel saving MID SAPS super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particle Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system.

Product Code: 78260

Engine Oil Super SHPD 10W-40 is formulated with high refined synthetic technology base stock in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against "Bore Polishing".
- Extended drain intervals.
- Complies with strictest European emission regulation.

Engine Oil Super SHPD 10W-40 exceeds the following performance criteria:

| Approved | Volvo VDS 4.5 | Mack EOS-4.5 | Renault VI RLD-3 |
|----------|-----------------------------------------------------------------|-----------------------------------------------------------|-----------------------------------------------------|
| Exceeds | API CK-4 MB 228.51 MAN M3775 MTU Type 3.1 JASO DH-2 | ACEA E7/E8/E11 Cummins CES 20086 DDC93K222 IVECO | MB 228.31 Deutz DQC IV-18 LA CAT ECF-3 DAF |

Typical Analysis

| Properties | | Unit | | Method | | Typical Value | |
|-----------------------------------|-------|-------------|------------|------------|--------|---------------|--|
| | | | | | | | |
| SAE Grade | | SAE J300 | | 10W-40 | | | |
| Density @15°C | | kg/m³ | ASTM D4052 | | 862 | | |
| Kin. Viscosity @40°C | mm²/s | ASTM D7042 | | | 98 | | |
| Kin. Viscosity @100°C | | mm²/s | ASTM D7042 | | | 14.6 | |
| Viscosity Index | | | ASTM D2270 | | | 154 | |
| Viscosity CCS @-25°C | | сР | ASTM D5293 | | | 5850 | |
| Flash Point COC | | °C | ASTM D92 | | | >201 | |
| Pour Point | | °C | ASTM D7346 | | | -36 | |
| Total Base Number | | mgKOH/g | ASTM D2896 | | | 10.1 | |
| Sulphated Ash | | %Wt | ASTM D874 | | | 0.96 | |
| Date Issued: 10-7-2024 Supersedes | | : 17-6-2024 | | Revision N | r.: 10 | | |