



Motor Oil Synth SL 0W-30
Fully-Synthetic Passenger Car Motor Oil

Product Code: 79600

Motor Oil Synth SL 0W-30 is an universal very high performance engine oil based on fully synthetic base oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

Motor Oil Synth SL 0W-30 is formulated with high quality synthetic and PAO (Poly-alpha-olefin) base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Motor Oil Synth SL 0W-30 meets the following performance criteria:

Approved: Volvo VCC 95200356

Meets: API SL ACEA A3/B4-16 MB 229.5
VW 502.00/505.00 Renault RN 0700/0710

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W-30
Density @15°C	kg/m ³	ASTM D4052	844
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	69
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.4
Viscosity Index		ASTM D2270	180
Viscosity CCS @-35°C	cP	ASTM D5293	5700
Flash Point COC	°C	ASTM D92	>210
Pour Point	°C	ASTM D7346	-51
Total Base Number	mgKOH/g	ASTM D2896	10.1

Date Issued: 4-5-2021	Supersedes: 26-02-2021	Revision Nr.: 02
-----------------------	------------------------	------------------