



Motor Oil Ultra PAO 0W-40

Product Code:79670

Fully Synthetic Passenger Car Motor Oil

Motor Oil Ultra PAO 0W-40 is a high performance fuel saving fully synthetic engine oil to be used in gasoline- and diesel engines of the latest generation passenger car and light vans with or without turbo compressor.

Motor Oil Ultra PAO 0W-40 is formulated with high quality fully synthetic base oils, PolyAlphaOlefin (PAO), in combination with a special selected additive package to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam en corrosion.
- High viscosity index in a wide range of ambient conditions.
- Low temperature properties, to ensure a smooth cold start.

Motor Oil Ultra PAO 0W-40 meets the following performance criteria;

| | | | |
|--------------|---------------------------------------|--------------------------------------|---|
| Meets | ACEA A3/B4 Porsche A40 MB 229.5 | API SN BMW LL-01 Ford M2C937-A | VW 502.00/505.00 Renault RN0700/0710 |
|--------------|---------------------------------------|--------------------------------------|---|

Typical Analysis

| Property | Unit | Method | Typical Value |
|-----------------------|--------------------|------------|---------------|
| SAE Grade | | SAE J300 | 0W-40 |
| Density @15°C | kg/m ³ | ASTM D4052 | 841 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 78.3 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 14.0 |
| Viscosity Index | | ASTM D2270 | 186 |
| Viscosity @-35°C | cP | ASTM D5293 | 5700 |
| HTHS @150°C | mPA*s | ASTM D4683 | 3.8 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D7346 | -57 |
| Total Base Number | mgKOH/g | ASTM D2896 | 10.4 |

| | | |
|-------------------------|-------------|----------------|
| Date Issued: 19-05-2021 | Supersedes: | Revision Nr. - |
|-------------------------|-------------|----------------|