

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 21/06/2012 Revision date: 15/01/2024 Supersedes version of: 13/07/2023 Version: 3.8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

1.1. Floudet identifier

Product form

Product name Product code

:	Mixture
:	76210 - Engine Oil HDX 15W-40
:	76210

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public Main use category Function or use category

: Industrial use, Professional use, Consumer use

: Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Transnational Blenders bv Wieldrechtseweg, 37 NL– 3316 BG Dordrecht – Netherlands Zuid Holland Netherlands T +31 (0)78 6527652 technical@tnb.nl - www.tnb.nl

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]		
EUH-statements	: EUH210 - Safety data sheet available on request.	
2.3. Other hazards		
Other hazards which do not result in classification	: Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.	

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627- 25	≥ 75 – < 90	Not classified
Distillates (petroleum), hydrotreated light paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077- 29	≥3-<5	Not classified
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299- 27	≥1-<3	Not classified
Distillates (petroleum), solvent-refined heavy paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64741-88-4 EC-No.: 265-090-8 EC Index-No.: 649-454-00-7 REACH-no: 01-2119488706- 23	≥ 0.3 - < 3	Not classified
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 Full text of H- and EUH-statements: see section 16	EC-No.: 701-251-5 REACH-no: 01-2119524004- 56	≥ 0.3 – < 3	Aquatic Chronic 4, H413

SECTION 4: First aid measures

4.1. Description of first aid measures	
First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact First-aid measures after ingestion	 Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Rinse eyes with water as a precaution. Call a poison center or a doctor if you feel unwell.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/effects	: After adequate first aid, no further treatment is required unless symptoms reappear.	
Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear.	
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear.	
Symptoms/effects after eye contact	: After adequate first aid, no further treatment is required unless symptoms reappear.	
Symptoms/effects after ingestion	: After adequate first aid, no further treatment is required unless symptoms reappear.	

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures			
5.1. Extinguishing media			
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Do not use a water jet since it may cause the fire to spread.		
5.2. Special hazards arising from the subst	ance or mixture		
Fire hazard Explosion hazard	 Will ignite if exposed to intensive heat. Not expected to be a fire/explosion hazard under normal conditions of use. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. 		
Reactivity in case of fire	 Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases. 		
Hazardous decomposition products in case of fire	: Toxic fumes may be released.		
5.3. Advice for firefighters			
Precautionary measures fire Firefighting instructions	 Evacuate area. Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. 		
Protection during firefighting	 Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. 		

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equipm	nent and emergency procedures		
General measures	: Spill area may be slippery. Prevent soil and water pollution. Prevent entry to sewers and public waters.		
6.1.1. For non-emergency personnel			
Protective equipment Emergency procedures	 Wear recommended personal protective equipment. Ventilate spillage area. Evacuate unnecessary personnel. Avoid any direct contact with the product. Stop leaks if it can be done without personal risk. 		
6.1.2. For emergency responders			
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".		
6.2. Environmental precautions			
Avoid release to the environment.			
6.3. Methods and material for containment and cleaning up			
	 For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Take up liquid spill into absorbent material. Clear up spills immediately and dispose of waste safely. Sweep or shovel spills into appropriate container for disposal. This material and its container must be disposed of in a safe way, and as per local legislation. May be reused following decontamination. Clean contaminated surfaces with an excess of water. 		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Other information

: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storag	je
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling	 Empty containers retain product residue and can be hazardous. Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Do not ingest. Do not breathe fumes from fires or vapours from decomposition. Avoid breathing dust, fume, gas, mist, spray, vapours. Ensure good ventilation of the work station. Spilled material may present a slipping hazard. Clean spills promptly.
Handling temperature Hygiene measures	 ≤ 40 °C Routine housekeeping should be instituted. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, incl	luding any incompatibilities
Technical measures Storage conditions	 Provide local exhaust or general room ventilation. Store in a well-ventilated place. Keep cool. Store away from oxidising agents. Protect from sunlight. Store in original container. Always keep in containers made of the same material as the supply container. Do not store in open, inadequate, mislabled packaging. Opened containers must be carefully closed and kept upright to avoid leakage. Empty containers should be taken for recycling, recovery or waste in accordance with local regulation. Empty containers retain product residue and can be hazardous. Store in a well-ventilated place. Keep cool.
Storage temperature	: ≤ 40 °C
Information on mixed storage Storage area	 Store away from strong oxidizers, strong bases, strong acids. Store at ambient temperature.
Special rules on packaging	: Keep container tightly closed and dry.

7.3. Specific end use(s)

Lubricant.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³	
IOEL STEL	10 mg/m³	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³	
WEL STEL (OEL STEL)	10 mg/m ³	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m³	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m ³	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m³	
Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)		
EU - Indicative Occupational Exposure Limit (IOEL)		
IOEL TWA	5 mg/m ³	
IOEL STEL	10 mg/m ³	
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA) [1]	5 mg/m ³	
WEL STEL (OEL STEL)	10 mg/m ³	

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Use adequate ventilation to keep oil mist below applicable standard. Use splash goggles when eye contact due to splashing is possible. Ocular shower with suitable liquid. Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses. Protective clothing.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Use splash goggles when eye contact due to splashing is possible. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Avoid prolonged and repeated contact with skin. If repeated skin contact or contamination of clothing is likely, protective clothing should be worn

Hand protection:

Breakthrough time : refer to the recommendations of the supplier

Other skin protection

Materials for protective clothing:

Wear suitable protective clothing

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.3. Respiratory protection

Respiratory protection:

Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment. Particle filter. EN 143

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: brown.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: -33 °C (ASTM D7346)
Boiling point	: Not available
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 225 °C (ASTM D92)
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
рН	: Not available
Viscosity, kinematic	: 105 mm²/s @ 40°C (ASTM D7042)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 863 kg/m³ @ 15°C (ASTM D4052)
Relative density	: Not available
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity (dermal) :	Not classified Not classified Not classified	
Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test	
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test	
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test	
Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test	
LD50 dermal (rabbit)	> 2000 mg/kg 402 Acute Dermal Toxicity Test	
LC50 inhalation (rat) (mg/l)	> 5000 mg/l/4h	
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test	
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)	
LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test	
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test	
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test	
Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)		
LD50 oral (rat)	> 5000 mg/kg	
LD50 dermal (rabbit)	> 2000 mg/kg	
LC50 inhalation (rat) (mg/l)	> 5000 mg/m³	
LC50 inhalation (rat) (Vapours - mg/l/4h)	5.53 mg/l/4h	
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50		
LD50 oral (rat)	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal (rabbit)	> 4000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LC50 inhalation (rat) (mg/l)	> 1.67 mg/l OECD 403 (1h)	
Serious eye damage/irritation:Respiratory or skin sensitisation:	Not classified Not classified Not classified Not classified	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Carcinogenicity : Not classified Reproductve toxicity : Not classified STOT-single exposure : Not classified STOT-single exposure : Not classified Distillates (petroleum), solvent-dewaxed he>ry paraffinic (64742-65-0) LOAEL (oral, rat. 90 days) : 125 mg/kg bodyweight : Distillates (petroleum), hydrotreated heavy paraffinic (64742-55-7) LOAEL (oral, rat. 90 days) : 125 mg/kg bodyweight Animal: rat. Animal sex: male, Guideline: OECD Guideline 408 (Repeated Doss 90-Dg/Carl Toxicity in Rodernia) Phenol, paraalkylation products with C10-15 branched olefinis (C12 rich) derived from propene oligomerization, carbonates, calcium saits, overbased, suffinized including distillates (petroleum), hydrotreated light paraffinic (64742-55-9) LOAEL (oral, rat, 90 days) : 200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Doss 90-Dg/Carl Toxicity in Rodernia) Phenol, paraalkylation products with C10-15 branched olefinis (C12 rich) derived from propene oligomerization, carbonates, calcium saits, overbased, suffinized including distillates (petroleum), hydrotreated, solvent- dewaxed, or catalytic dewaxed, light or heavy paraffinic (C15-C50 NOAEL (ceni, rat, 90 days) : 200 mg/kg bodyweight Animai: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Sudy with the Reproduction / Developmental Toxicity Screening Test) NOAEL (demail, rat/rabbit, 90 days) : 220 mg/kg bodyweight Animai: rat, Guideline: OECD Guideline 420 Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic : 105 mm ² /kg 40°C Distillates (petroleum), hydrotreated heavy paraffinic (64742-65-8) Viscosity, kinematic : 28.5 mm ² /kg 40°C Distillates (potroleum), hydrotreated light partifinic (64742-65-8) Viscosity, kinematic : 28.5 mm ² /kg 40°C Distillates (potroleum), hydrotreated light partifinic (64742-65-8) Viscosity, kinematic : 28.5 mm ² /kg 40°C Phenol, paraalkylation products with C10-15 branched olefinis (C12 rich) derived fr	according to the REACH Regulation (EC) 1907/2006 amended	by Regulation (EU) 2020/878	
LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Dral Toxicity in Rodents) Phenol, paraalkylation products with C10-15b branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium satis, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent- dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 NOAEL (oral, rat, 90 days) 200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbil, 90 days) = 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Aspiration hazard : Not classified 76210 - Engine Oil HDX 15W-40 105 mm²/s @ 40°C (ASTM D7042) Viscosity, kinematic 105 mm²/s @ 40°C Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic = 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-56-8) </td <td>Reproductive toxicity:STOT-single exposure:</td> <td>Not classified Not classified</td>	Reproductive toxicity:STOT-single exposure:	Not classified Not classified	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 NOAEL (oral, rat, 90 days) 200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (200mlone Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbit, 90 days) = 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Demai Toxicity: 21/28-Day Study) Aspiration hazard : Not classified 76210 - Engine Oil HDX 15W-40 105 mm ⁴ /s @ 40°C (ASTM D7042) Viscosity, kinematic 105 mm ⁴ /s @ 40°C Distillates (petroleum), hydrotreated heavy paraffinic (64742-56-8) Viscosity, kinematic ≤ 20.5 mm ⁴ /s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-56-8) Viscosity, kinematic ≈ 98 mm ⁴ /s @ 40°C Distill	Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 NOAEL (oral, rat, 90 days) 200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbit, 90 days) 200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbit, 90 days) * 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Aspiration hazard : Not classified 76210 - Engine Oil HDX 15W-40 Viscosity, kinematic Viscosity, kinematic 105 mm ² /s @40°C (ASTM D7042) Distillates (petroleum), hydrotreated heavy paraffinic (64742-65-0) Viscosity, kinematic Viscosity, kinematic = 98 mm ² /s @40°C	LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight	
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Phenol, paraalkylation products with C10-15 branched olefins (C12 rlch) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, rat, 90 days) NOAEL (oral, rat, 90 days) 200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbi, 90 days) = 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermai Toxicity: 21:28-Day Study) Aspiration hazard : Not classified 76210 - Engine Oii HDX 15W-40 105 mm²/s @ 40°C (ASTM D7042) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Distillates (petroleum), hydrotreated leght paraffinic (64742-55-8) Viscosity, kinematic Viscosity, kinematic < 20.5 mm²/s @40°C	Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
LOAEL (oral, rat, 90 days) 125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy parafflin C C15-C50 NOAEL (oral, rat, 90 days) 200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbit, 90 days) ± 200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbit, 90 days) ± Not classified 76210 - Engine OII HDX 15W-40 Uiscosity, kinematic 105 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), solvent-dewaxed heavy parafflinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @ 40°C Distillates (petroleum), hydrotreated heavy parafflinic (64742-55-8) Viscosity, kinematic = 98 mm²/s @ 40°C Distillates (petroleum), solvent-refined heavy parafflinic (64741-88-4) Viscosity, kinematic 28.51 mm²/s @40°C Distillates (petroleum), solvent-refined heavy parafflinic (C12 rich) derived from propene oligomerization, carbonates,	LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408	
(Repeated Dose 90-Day Oral Toxicity in Rodents) Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 NOAEL (oral, rat, 90 days) 200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbit, 90 days) = 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Dombined Repeated Dose Dermal Toxicity: 21/28-Day Study) Aspiration hazard : Not classified 76210 - Engine Oil HDX 15W-40 Viscosity, kinematic Viscosity, kinematic 105 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic Viscosity, kinematic = 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic Viscosity, kinematic < 20.5 mm²/s @ 40°C	Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)	
carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 NOAEL (oral, rat, 90 days) 200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbit, 90 days) = 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Aspiration hazard : Not classified 76210 - Engine Oil HDX 15W-40 Viscosity, kinematic Viscosity, kinematic 105 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic = 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @ 40°C	LOAEL (oral, rat, 90 days)		
(Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) NOAEL (dermal, rat/rabbit, 90 days) = 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) Aspiration hazard : Not classified 76210 - Engine Oil HDX 15W-40 Viscosity, kinematic Viscosity, kinematic 105 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic Viscosity, kinematic 150 (1.99 – 847) mm²/s @ 40°C Distillates (petroleum), hydrotreated heavy paraffinic (64742-55-0) Viscosity, kinematic Viscosity, kinematic = 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic Viscosity, kinematic < 20.5 mm²/s @ 40°C	carbonates, calcium salts, overbased, sulfuri	zed including distillates (petroleum), hydrotreated, solvent-refined, solvent-	
Dermal Toxicity: 21/28-Day Study) Aspiration hazard : Not classified 76210 - Engine Oil HDX 15W-40 Viscosity, kinematic 105 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic ≈ 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic ≈ 98 mm²/s @40°C Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4) Viscosity, kinematic 28.51 mm²/s @40°C Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 Viscosity, kinematic 206820 mm²/s Temp.: '20°C' Parameter: 'cSt' 11.2. Information on other hazards 206820 mm²/s Temp.: '20°C' Parameter: 'cSt'	NOAEL (oral, rat, 90 days)	(Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity	
76210 - Engine Oil HDX 15W-40 Viscosity, kinematic 105 mm²/s @ 40°C (ASTM D7042) Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 - 847) mm²/s @40°C Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic ≈ 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C	NOAEL (dermal, rat/rabbit, 90 days)		
Viscosity, kinematic105 mm²/s @ 40°C (ASTM D7042)Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)Viscosity, kinematic150 (1.99 – 847) mm²/s @40°CDistillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)Viscosity, kinematic≈ 98 mm²/s @ 40°CDistillates (petroleum), hydrotreated light paraffinic (64742-55-8)Viscosity, kinematic≈ 98 mm²/s @ 40°CDistillates (petroleum), hydrotreated light paraffinic (64742-55-8)Viscosity, kinematic< 20.5 mm²/s @ 40°CDistillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)Viscosity, kinematic28.51 mm²/s @40°CPhenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent- dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50Viscosity, kinematic206820 mm²/s Temp.: '20°C' Parameter: 'cSt'11.2. Information on other hazards	Aspiration hazard :	Not classified	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0) Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic ≈ 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C	76210 - Engine Oil HDX 15W-40		
Viscosity, kinematic 150 (1.99 – 847) mm²/s @40°C Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic ≈ 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C	Viscosity, kinematic	105 mm²/s @ 40°C (ASTM D7042)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7) Viscosity, kinematic ≈ 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C	Distillates (petroleum), solvent-dewaxed heav	y paraffinic (64742-65-0)	
Viscosity, kinematic ≈ 98 mm²/s @ 40°C Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C	Viscosity, kinematic	150 (1.99 – 847) mm²/s @40°C	
Distillates (petroleum), hydrotreated light paraffinic (64742-55-8) Viscosity, kinematic < 20.5 mm²/s @40°C	Distillates (petroleum), hydrotreated heavy pa	araffinic (64742-54-7)	
Viscosity, kinematic < 20.5 mm²/s @40°C	Viscosity, kinematic	≈ 98 mm²/s @ 40°C	
Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4) Viscosity, kinematic 28.51 mm²/s @40°C Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 Viscosity, kinematic 206820 mm²/s Temp.: '20°C' Parameter: 'cSt' 11.2. Information on other hazards	Distillates (petroleum), hydrotreated light par	affinic (64742-55-8)	
Viscosity, kinematic 28.51 mm²/s @40°C Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 Viscosity, kinematic 206820 mm²/s Temp.: '20°C' Parameter: 'cSt' 11.2. Information on other hazards	Viscosity, kinematic	< 20.5 mm²/s @40°C	
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 Viscosity, kinematic 206820 mm²/s Temp.: '20°C' Parameter: 'cSt' 11.2. Information on other hazards	Distillates (petroleum), solvent-refined heavy	paraffinic (64741-88-4)	
carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50 Viscosity, kinematic 206820 mm²/s Temp.: '20°C' Parameter: 'cSt' 11.2. Information on other hazards	Viscosity, kinematic	28.51 mm²/s @40°C	
11.2. Information on other hazards	carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-		
	Viscosity, kinematic	206820 mm²/s Temp.: '20°C' Parameter: 'cSt'	
No additional information available	11.2. Information on other hazards		
	No additional information available		

 SECTION 12: Ecological information

 12.1. Toxicity

 Ecology - general
 : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

 Hazardous to the aquatic environment, short-term (acute)
 : Not classified

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous to the aquatic environment, long–term : Not classified (chronic)		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
LC50 - Fish [1]	> 100 mg/l Pimephales promelas	
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna	
NOEC chronic fish	> 1000 mg/l Oncorhynchus mykiss (14d)	
NOEC chronic crustacea	> 10 mg/l Daphnia magna (21d)	
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata (72h)	
Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)		
LC50 - Fish [1]	> 100 mg/l Pimephales promelas	
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna	
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitat	
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)	
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)	
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)	
Distillates (petroleum), hydrotreated light para	affinic (64742-55-8)	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas	
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna	
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitat	
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)	
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)	
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)	
Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)		
LC50 - Fish [1]	> 100 mg/l Pimephales promelas	
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna	
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)	
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)	
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)	
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50		
LC50 - Fish [1]	> 1000 mg/l Pimephales promelas	
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna	
EC50 96h - Algae [1]	> 500 mg/l Pseudokirchneriella subcapitata	
12.2. Persistence and degradability		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)		
Biodegradation	31 % OECD 301F (28d)	
Distillates (petroleum), hydrotreated heavy pa	raffinic (64742-54-7)	
Persistence and degradability	Not readily biodegradable.	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ne oligomerization, ted, solvent-refined, solvent-		
ne oligomerization, ted, solvent-refined, solvent-		
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50		

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods Sewage disposal recommendations Product/Packaging disposal recommendations	 Dispose of contents/container in accordance with licensed collector's sorting instructions. Disposal must be done according to official regulations. Recycle product or dispose safely. Recycle the material as far as possible. Recycle or dispose of in compliance with current legislation. 	
European List of Waste (LoW, EC 2000/532)	: 13 02 05* - mineral-based non-chlorinated engine, gear and lubricating oils	
SECTION 14: Transport information		
In accordance with ADR / IMDG / IATA / ADN / RI	D	

ADR	IMDG	ΙΑΤΑ	ADN	RID
I4.1. UN number or ID n	umber		· · · · ·	
Not regulated for transport				
I4.2. UN proper shipping	g name			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
I4.3. Transport hazard c	lass(es)			
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
I4.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental haz	ards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No

14.6. Special precautions for user

Overland transport No data available

Transport by sea No data available

Air transport No data available

Inland waterway transport No data available

Rail transport No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
2.2	Precautionary statements (CLP)	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:		
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
ΙΑΤΑ	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
РВТ	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH-statements:		
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4	
EUH210	Safety data sheet available on request.	
H413	May cause long lasting harmful effects to aquatic life.	

The classification complies with

: ATP 8

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.