

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : 76260 - Engine Oil Super SHPD 15W-40  
Product code : 76260

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional use, Consumer use  
Function or use category : Lubricants and additives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Transnational Blenders bv  
Wieldrechtseweg, 37  
NL- 3316 BG Dordrecht – Netherlands Zuid Holland  
Netherlands  
T +31 (0)78 6527652  
[technical@tnb.nl](mailto:technical@tnb.nl) - [www.tnb.nl](http://www.tnb.nl)

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER	+44 20 7188 7188	
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA	0344 892 0111	Only for healthcare professionals

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH210 - Safety data sheet available on request.

#### 2.3. Other hazards

Other hazards which do not result in classification : Flammable liquids. Prolonged or repeated skin contact with the material will remove natural oils which leads to a dermatitis. Spills of this product present a serious slipping hazard.

Contains no PBT and/or vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil substance with a Community workplace exposure limit	CAS-No.: 72623-87-1 EC-No.: 276-738-4 EC Index-No.: 649-483-00-5 REACH-no: 01-2119474889-13	≥ 75 – < 90	Asp. Tox. 1, H304
Distillates (petroleum), hydrotreated heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-54-7 EC-No.: 265-157-1 EC Index-No.: 649-467-00-8 REACH-no: 01-2119484627-25	≥ 3 – < 10	Not classified
Distillates (petroleum), hydrotreated light paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64742-55-8 EC-No.: 265-158-7 EC Index-No.: 649-468-00-3 REACH-no: 01-2119487077-29	≥ 1 – < 3	Not classified
Distillates (petroleum), solvent-dewaxed heavy paraffinic substance with national workplace exposure limit(s) (AT, BE, BG, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 64742-65-0 EC-No.: 265-169-7 EC Index-No.: 649-474-00-6 REACH-no: 01-2119471299-27	≥ 0.3 – < 3	Not classified
Alkyl esters of alkyl phenate alkanolic acid	-	≥ 0.3 – < 3	Aquatic Chronic 4, H413
Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50	EC-No.: 701-251-5 REACH-no: 01-2119524004-56	≥ 0.3 – < 3	Aquatic Chronic 4, H413
Distillates (petroleum), solvent-refined heavy paraffinic substance with national workplace exposure limit(s) (BE, BG, CZ, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, LT, LV, NL, PL, PT, RO, SE, SI, SK, IS, NO, CH); substance with a Community workplace exposure limit	CAS-No.: 64741-88-4 EC-No.: 265-090-8 EC Index-No.: 649-454-00-7 REACH-no: 01-2119488706-23	≥ 0.3 – < 3	Not classified

Full text of H- and EUH-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after inhalation	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after skin contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after eye contact	: After adequate first aid, no further treatment is required unless symptoms reappear.
Symptoms/effects after ingestion	: After adequate first aid, no further treatment is required unless symptoms reappear.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--------------------------------------------------	--------------------------------

### 5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire.
Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid spilling the product, as this might cause falls.
------------------	----------------------------------------------------------

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with skin and eyes.
Handling temperature	: ≤ 40 °C
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Provide local exhaust or general room ventilation.
Storage conditions	: Keep only in the original container in a cool, well ventilated place away from : Heat sources, Direct sunlight. Store in a well-ventilated place. Keep cool.
Storage temperature	: ≤ 40 °C
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Keep only in original container. Store in a closed container.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

###### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
----------	---------------------

###### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
-----------------------	---------------------

###### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
----------	---------------------

###### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
-----------------------	---------------------

###### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>

###### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

###### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>

###### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup>

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

#### EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	5 mg/m <sup>3</sup>
IOEL STEL	10 mg/m <sup>3</sup>

#### United Kingdom - Occupational Exposure Limits

WEL TWA (OEL TWA) [1]	5 mg/m <sup>3</sup>
WEL STEL (OEL STEL)	10 mg/m <sup>3</sup>

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

No additional information available

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### 8.2.2. Personal protection equipment

##### Personal protective equipment:

Gloves. Safety glasses. Protective clothing.

##### Personal protective equipment symbol(s):



##### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### Eye protection

Type	Field of application	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

##### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR), Neoprene rubber (HNBR)	6 (> 480 minutes)	0.35		EN ISO 374

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### 8.2.2.3. Respiratory protection

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light brown.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -36 °C (ASTM D7346)
Boiling point	: No data available
Flash point	: > 201 °C (ASTM D92)

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 866 kg/m <sup>3</sup> @ 15°C (ASTM D4052)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 104 mm <sup>2</sup> /s @ 40°C (ASTM D7042)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Strong oxidizing agents.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral) : Not classified  
Acute toxicity (dermal) : Not classified  
Acute toxicity (inhalation) : Not classified

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 2000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (mg/l)	> 5000 mg/l/4h
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

LD50 oral (rat)	> 5000 mg/kg 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)

LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (Dust/Mist - mg/l/4h)	> 5.53 mg/l/4h

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

LD50 oral (rat)	> 5000 mg/kg bodyweight 401 Acute Oral Toxicity Test
LD50 dermal (rabbit)	> 5000 mg/kg 402 Acute Dermal Toxicity Test
LC50 inhalation (rat) (Vapours - mg/l/4h)	> 5.53 mg/l/4h 403 Acute Inhalation Toxicity Test

#### Alkyl esters of alkyl phenate alkanolic acid

LD50 oral (rat)	> 2000 mg/kg 401 Acute Oral Toxicity
LD50 dermal (rat)	> 2000 mg/kg 402 Acute Dermal Toxicity

#### Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50

LD50 oral (rat)	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal (rabbit)	> 4000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation (rat) (mg/l)	> 1.67 mg/l OECD 403 (1h)

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
LD50 oral (rat)	> 5000 mg/kg
LD50 dermal (rabbit)	> 2000 mg/kg
LC50 inhalation (rat) (mg/l)	> 5000 mg/m <sup>3</sup>
LC50 inhalation (rat) (Vapours - mg/l/4h)	5.53 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408
<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight/day
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
LOAEL (oral, rat, 90 days)	125 mg/kg bodyweight
<b>Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50</b>	
NOAEL (oral, rat, 90 days)	200 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (dermal, rat/rabbit, 90 days)	≈ 250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
Aspiration hazard	: Not classified
<b>76260 - Engine Oil Super SHPD 15W-40</b>	
Viscosity, kinematic	104 mm <sup>2</sup> /s @ 40°C (ASTM D7042)
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Viscosity, kinematic	≈ 98 mm <sup>2</sup> /s @ 40°C
<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
Viscosity, kinematic	< 20.5 mm <sup>2</sup> /s @40°C
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)</b>	
Viscosity, kinematic	47 mm <sup>2</sup> /s
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
Viscosity, kinematic	150 (1.99 – 847) mm <sup>2</sup> /s @40°C



# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

**Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50**

Viscosity, kinematic 206820 mm<sup>2</sup>/s Temp.: '20°C' Parameter: 'cSt'

**Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)**

Viscosity, kinematic 28.51 mm<sup>2</sup>/s @40°C

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

**Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)**

LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)

**Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)**

LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)

**Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)**

LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	100 mg/l Pseudokirchneriella subcapitata (72h)

**Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)**

LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	> 1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	> 10 mg/l Daphnia magna (21d)

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
NOEC chronic algae	> 100 mg/l Pseudokirchneriella subcapitata (72h)
<b>Alkyl esters of alkyl phenate alkanolic acid</b>	
LC50 - Fish [1]	> 74 mg/l Danio rerio
EC50 - Crustacea [1]	> 0.9 mg/l Daphnia magna
EC50 72h - Algae [1]	> 3 mg/l Desmodesmus subspicatus
NOEC chronic fish	> 0.001 mg/l Danio rerio (36d)
NOEC chronic algae	> 3 mg/l Desmodesmus subspicatus (72h)
<b>Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50</b>	
LC50 - Fish [1]	> 1000 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 1000 mg/l Daphnia magna
EC50 96h - Algae [1]	> 500 mg/l Pseudokirchneriella subcapitata
<b>Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)</b>	
LC50 - Fish [1]	> 100 mg/l Pimephales promelas
EC50 - Crustacea [1]	> 10000 mg/l Daphnia magna
NOEC chronic fish	1000 mg/l Oncorhynchus mykiss (14d)
NOEC chronic crustacea	10 mg/l Daphnia magna (21d)
NOEC chronic algae	≥ 100 mg/l Pseudokirchneriella subcapitata (72h)
<b>12.2. Persistence and degradability</b>	
<b>Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % OECD TG 301 F (28d)
<b>Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)</b>	
Biodegradation	31 % OECD TG 301 F (28d)
<b>Lubricating oils (petroleum), C20-50, hydrotreated neutral oil (72623-87-1)</b>	
Biodegradation	31 %
<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)</b>	
Biodegradation	31 % OECD 301F (28d)
<b>Alkyl esters of alkyl phenate alkanolic acid</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	2 % OECD 301B (28d)
<b>Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50</b>	
Persistence and degradability	Not readily biodegradable.
Biodegradation	13.4 % OECD 301B (28d)

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

Persistence and degradability	Not readily biodegradable.
Biodegradation	31 % OECD 301F (28d)

### 12.3. Bioaccumulative potential

#### Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6
-------------------------------------------------	---------

#### Distillates (petroleum), hydrotreated light paraffinic (64742-55-8)

Partition coefficient n-octanol/water (Log Pow)	> 6
-------------------------------------------------	-----

#### Distillates (petroleum), solvent-dewaxed heavy paraffinic (64742-65-0)

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

#### Alkyl esters of alkyl phenate alkanolic acid

Bioconcentration factor (BCF REACH)	260
-------------------------------------	-----

Partition coefficient n-octanol/water (Log Pow)	9.2
-------------------------------------------------	-----

#### Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50

Bioconcentration factor (BCF REACH)	2.2
-------------------------------------	-----

Partition coefficient n-octanol/water (Log Pow)	9.5
-------------------------------------------------	-----

#### Distillates (petroleum), solvent-refined heavy paraffinic (64741-88-4)

Partition coefficient n-octanol/water (Log Pow)	3.9 – 6
-------------------------------------------------	---------

### 12.4. Mobility in soil

#### Phenol, paraalkylation products with C10-15 branched olefins (C12 rich) derived from propene oligomerization, carbonates, calcium salts, overbased, sulfurized including distillates (petroleum), hydrotreated, solvent-refined, solvent-dewaxed, or catalytic dewaxed, light or heavy paraffinic C15-C50

Mobility in soil	3615000000000 Source: EPISUITE
------------------	--------------------------------

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW, EC 2000/532)	: 13 02 00 - waste engine, gear and lubricating oils
HP Code	: HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

###### REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

###### REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

###### REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

###### PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

### POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

### Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

### Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

### Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
2.1	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Modified	
9.1	Colour	Modified	

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose

# 76260 - Engine Oil Super SHPD 15W-40

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2015/830

Abbreviations and acronyms:	
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Full text of H- and EUH-statements:	
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH210	Safety data sheet available on request.
H304	May be fatal if swallowed and enters airways.
H413	May cause long lasting harmful effects to aquatic life.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.