



Motor Oil SL 10W-40

Product Code: 76060

Motor Oil SL 10W-40 is an universal high performance fuel saving semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

Motor Oil SL 10W-40 is formulated with high quality refined mineral and synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Motor Oil SL 10W-40 meets the following performance criteria:

ACEA A3/B3

API SN

MB 229.1

VW 501.01/505.00

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15°C	kg/m ³	ASTM D4052	854.8
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	88.2
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.9
Viscosity Index		ASTM D2270	161
HTHS viscosity @150°C	mPa.s	ASTM D4683	3.9
Viscosity CCS @-25°C	cP	ASTM D5293	4510
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.5
Sulphated Ash	%wt	ASTM D874	1.1

Date Issued: 27-11-2024	Supersedes: 02-08-2022	Revision Nr.: 06
-------------------------	------------------------	------------------