



Motor Oil SL 15W-40

Product Code: 76100

Mineral Passenger Car Motor Oil

MOTOR OIL SL 15W-40 is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.

MOTOR OIL SL 15W-40 is based on high performance virgin mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.

MOTOR OIL SL 15W-40 exceeds the following performance criteria:

ACEA A3/B3

API SN

MB 229.1

VW 501.01/505.00

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m ³	ASTM D4052	859.6
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	88.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.8
Viscosity Index		ASTM D2270	152
HTHS viscosity @150°C	mPa.s	ASTM D4683	3.9
Viscosity CCS -20°C	cP	ASTM D5293	3380
Flash Point COC	°C	ASTM D92	220
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	9.5
Sulphated Ash	%Wt	ASTM D874	1.1

Date Issued: 27-11-2024	Supersedes: 03-08-2022	Revision Nr.: 04
-------------------------	------------------------	------------------