



Motor Oil SF 15W-40

Product Code: 76110

Mineral Passenger Car Motor Oil

MOTOR OIL SF 15W-40 is a multi functional mineral engine oil for older gasoline-, diesel- and LGP engines of passenger car and light vans with or without turbo compressor.

MOTOR OIL SF 15W-40 is formulated on high performance virgin base stocks in combination with selected additive package to reach the following properties:

- Stable viscosity index.
- Good protection against rust, corrosion and wear.
- Good dispersency and detergency properties.
- Good antifoam properties.

MOTOR OIL SF 15W-40 exceeds the following performance criteria:

API SF/CD

Typical Analysis

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m ³	ASTM D4052	865.7
Kin. Viscosity @40°C	mm ² /s	ASTM D4052	93.7
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.6
Viscosity Index		ASTM D2270	146
Viscosity CCS -20°C	cP	ASTM D5293	3870
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Nummer	mgKOH/g	ASTM D2896	8.5

Date Issued: 27-11-2024	Supersedes: 22-2-2021	Revision Nr.: 03
-------------------------	-----------------------	------------------