



Motor Oil FS 5W-30

Product Code: 76120

Fully Synthetic Passenger Car Motor Oil

Motor Oil FS 5W-30 is a high performance fuel saving oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger and designed for the last generation Ford vehicles and other vehicles where an ACEA A5/B5 is been required. Except Ford this product is not to be used in diesel engines equipped with a Diesel Particle Filter (DPF).

Motor Oil FS 5W-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Longer oil drain interval.

Motor Oil FS 5W-30 meets the following performance criteria:

ACEA A5/B5	ACEA A1/B1	API SL	Renault 0700
Ford WSS M2C913C	Ford WSS M2C913D	VWC 53036	

Typical Analysis

Properties	Unit	Test Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m ³	ASTM D4052	849.6
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	56.6
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	10.3
Viscosity Index		ASTM D2270	172
Viscosity CCS @-30°C	cP	ASTM D5293	3850
Flash Point COC	°C	ASTM D92	210
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	9.9
Sulphated Ash	%Wt	ASTM D874	1.08

Date Issued: 27-11-2024	Supersedes: 25-10-2024	Revision Nr.: 05
-------------------------	------------------------	------------------