

Engine Oil HDX 10W-40

Product Code: 76200

Semi Synthetic Heavy Duty Diesel Engine Oil

Engine Oil HDX 10W-40 is an extra high performance universal semi synthetic engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. <u>This product is not suitable for vehicles equipped with DPF filters.</u>

Engine Oil HDX 10W-40 is formulated with high refined solvent mineral and synthetic base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

Engine Oil HDX 10W-40 meets the following performance criteria:

Approved	Mack EO-N DTFR 15B110 (MB 228.3)	Volvo VDS-3	Renault RLD-2
Meets	API CI-4 ACEA E7 Caterpillar ECF-1a, ECF-2 MB 229.1H Cummins CES 20077/20078 Mack EO-M+	API SL ACEA A3/B4 Global DHD-1 MTU Type 2 Voith retarder B	DDC 93K215 Deutz DQC-III-10 JASO DH-1 MAN M 3275 Allison TES-439

Pending MB 235.28

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15°C	kg/m ³	ASTM D4052	869.2
Kin. Viscosity @40°C	mm²/s	ASTM D7042	98.9
Kin. Viscosity @100°C	mm²/s	ASTM D7042	14.5
Viscosity Index		ASTM D2270	151
Viscosity CCS @-25°C	cP	ASTM D5293	6450
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	11.6
Sulphated Ash	%Wt	ASTM D874	1.5

Date Issued: 5-12-2024 Supersed

Supersedes: 02-03-2021 Revision Nr.: 05