



Engine Oil HDX 15W-40

Product Code: 76210

Mineral Heavy Duty Diesel Engine Oil

Engine Oil HDX 15W-40 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

Engine Oil HDX 15W-40 is formulated with high refined solvent mineral stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals.

Engine Oil HDX 15W-40 meets the following performance criteria:

Approved	DTRF 15B110 (MB 228.3) Mack EO-N	Volvo VDS-3	Renault RLD-2
Meets	API CI-4/ SL Caterpillar ECF-1a Deutz DQC-III Cummins CES 20077/20078	ACEA E7 Caterpillar ECF-2 MTU Type 2 Global DHD-1	MB 228.1 JASO DH-1 MAN M 3275 DDC 93K215

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m ³	ASTM D4052	886.3
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	99.8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.7
Viscosity Index		ASTM D2270	138
Viscosity CCS @-20°C	cP	ASTM D5293	5690
Flash Point COC	°C	ASTM D92	225
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	11.2
Sulphated Ash	%Wt	ASTM D874	1.5

Date Issued: 5-12-2024	Supersedes: 12-07-2022	Revision Nr.: 07
------------------------	------------------------	------------------