



Engine Oil HD 20W-50

Product Code:76240

Heavy Duty Diesel Engine Oil

Engine Oil HD 20W-50 is a high performance universal mineral engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year and is formulated for use in Euro-1, Euro-2 and Euro-3 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

Engine Oil HD 20W-50 is formulated on high refined solvent base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Not suitable for engine equipped with a Diesel Particulate Filter (DPF).

Engine Oil HD 20W-50 meets the following performance criteria:

API CG-4
Volvo VDS

ACEA E2
MTU Type 1

MB 228.1
Renault RD

M271

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	20W-50
Density @15°C	kg/m ³	ASTM D4052	886.9
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	156.9
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	18.8
Viscosity Index		ASTM D2270	130
Viscosity CCS @-15°C	cP	ASTM D5293	6720
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	8.6
Sulphated Ash	%Wt	ASTM D874	1.26

Date Issued: 6-12-2024	Supersedes: 03-03-2021	Revision Nr.: 05
------------------------	------------------------	------------------