



Motor Oil SL/CF 5W-30

Product Code: 78100

Semi Synthetic Motor Oil for passenger cars and light vans

Motor Oil SL/CF 5W-30 Semi Synthetic is a high performance semi synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbo compressor. This product is not to be used in diesel engines equipped with a Diesel Particle Filter (DPF).

Motor Oil SL/CF 5W-30 Semi Synthetic is formulated with re-refined mineral and synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Motor Oil SL/CF 5W-30 Semi Synthetic meets the following performance criteria:

API SL/CF

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m ³	ASTM D4052	851.7
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	64.6
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	11
Viscosity Index		ASTM D2270	163
Viscosity CCS @ -30°C	cP	ASTM D5293	5100
Flash Point COC	°C	ASTM D92	210
Pour Point	°C	ASTM D7346	-42
Total Base Number	mgKOH/g	ASTM D2896	7.7

Date Issued: 27-11-2024	Supersedes: 05-10-2021	Revision Nr.: 05
-------------------------	------------------------	------------------