



## Motor Oil SL 20W-50

Product Code: 78120

Mineral Passenger Car Motor Oil

**MOTOR OIL SL 20W-50** is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.

**MOTOR OIL SL 20W-50** is based on high performance virgin mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.

**MOTOR OIL SL 20W-50** exceeds the following performance criteria:

ACEA A3/B3

API SN

MB 229.1

VW 501.01/505.00

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	20W-50
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	869.5
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D7042	147.1
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D7042	18
Viscosity Index		ASTM D2270	136
Viscosity CCS -15°C	cP	ASTM D5293	5210
Flash Point COC	°C	ASTM D92	220
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	9.6
Sulphated Ash	%Wt	ASTM D874	1.1

Date Issued: 27-11-2024	Supersedes: 03-08-2022	Revision Nr.: 04
-------------------------	------------------------	------------------