



## Motor Oil Semi Synth SL 10W-40

Synthetic technology Passenger Car Motor Oil

Product Code: 78130

**Motor Oil Semi Synth SL 10W-40** is an universal high performance synthetic technology oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

**Motor Oil Semi Synth SL 10W-40** is formulated with high quality re-refined base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

**Motor Oil Semi Synth SL 10W-40** exceeds the following performance criteria:

ACEA SL/CF

ACEA A3/B3-08

MB 229.1

VW 501.01

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W-40
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	854.3
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	89.8
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	14.2
Viscosity Index		ASTM D2270	164
Viscosity CCS @-25	cP	ASTM D5293	3900
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	8.4

Date Issued: 27-11-2024

Supersedes: 10-10-2022

Revision Nr.: 06