

Motor Oil Synthetic DXI 5W-20

Product Code: 78150

Synthetic Passenger Car Motor Oil

Product Description:

Motor Oil Synthetic DXI 5W-20 is a high performance fuel saving engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a ILSAC GF-6A specification is required.

Motor Oil Synthetic DXI 5W-20 is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Excellent cold temperature properties for a smooth cold start.
- Very good dispersant and detergent properties.
- Fuel saving properties due to low friction properties
- Very good antifoam, anti-wear and anti-corrosion properties.
- Long oil change interval possible.

Motor Oil Synthetic DXI 5W-20 meets the following performance criteria:

API SP	API SN	API SN + RC	ILSAC GF-6A
Dexos1™ Gen 3	Ford WSS-M2C960-A1	GM 4718M	Chrysler MS-6395

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-20
Density @15°C	kg/m ³	ASTM D4052	850.7
Kin. Viscosity @40°C	mm²/s	ASTM D7042	47.9
Kin. Viscosity @100°C	mm²/s	ASTM D7042	8.6
Viscosity Index		ASTM D2270	160
Viscosity CCS @-30°C	cP	ASTM D5293	4530
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	8.6

Date Issued: 4-12-2024 Supersedes: 4-7-2024 Revision Nr.: 02