

Engine Oil Synthetic SHPD 5W-30

Product Code: 78265

Synthetic MID SAPS Heavy Duty Diesel Engine Oil

Engine Oil Synthetic SHPD 5W-30 is a fuel saving MID SAPS super high performance universal oil based on 100% synthetic technology designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-4, Euro-5 and Euro-6 engines equipped with a Diesel Particle Filter (DPF) and suited for diesel engines equipped with EGR and/or SCR after treatment system.

Engine Oil Synthetic SHPD 5W-30 is formulated with high refined synthetic base stock in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency. •
- High anti-foam, anti-wear and anti-corrosion properties. •
- Excellent protection against "Bore Polishing". •
- Extended drain intervals. •
- Complies with strictest European emission regulation.

Engine Oil Synthetic SHPD 5W-30 exceeds the following performance criteria:

Approved	Volvo VDS 4.5 DTFR 15C110 (MB 228	Mack EOS-4.5 3.51)	Renault VI RLD-3
Exceeds	API CK-4	ACEA E7/E8/E11	API SN
	CAT ECF-3	Scania LDF-4	MAN M3677
	MAN M3777	MAN M3775	Cummins CES 20086
	DFS 93K222	DAF	IVECO
	MTU 3.1	Deutz DQC IV-18-LA	JASO DH-2

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m ³	ASTM D4052	852.7
Kin. Viscosity @40°C	mm²/s	ASTM D7042	72.5
Kin. Viscosity @100°C	mm²/s	ASTM D7042	12.2
Viscosity Index		ASTM D2270	167
Viscosity CCS @-30°C	cP	ASTM D5293	5900
Flash Point COC	°C	ASTM D92	>205
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	9.6
Sulphated Ash	%Wt	ASTM D874	0.96
Date Issued: 6-12-2024	Supersedes: 10-7-2024	Peyision N	lr · 05

Supersedes: 10-7-2024

Revision Nr.: 05