



Motor Oil SG 15W-40

Product Code:78300

Mineral engine oil for gasoline- and diesel engines

Motor Oil SG 15W-40 is a high QUALITY mineral engine oil to be used in gasoline-, LPG-, and diesel engines in modern passenger car and light vans with or without turbochargers.

Motor Oil SG 15W-40 is based on high performance virgin mineral base oil in combination with a specially selected additive technology to ensure the following properties.

- Good dispersant and detergent properties.
- Good protection against forming of Bore Polishing.
- High resistance against corrosion and oxidation.
- Good resistance against wear and foam.

Motor Oil SG 15W-40 meets the following performance criteria;

API SG

API CF-4

Typical Analysis

Property	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15°C	kg/m ³	ASTM D4052	880
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	104.8
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.1
Viscosity Index		ASTM D2270	136
Viscosity CCS -20°C	Cp	ASTM D5293	6220
Flash Point COC	°C	ASTM D92	230
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOG/g	ASTM D2896	6.3
Sulphated Ash	%wt	ASTM D874	0.9

Date Issued: 28-11-2024	Supersedes: 23-02-2021	Revision Nr.: 04
-------------------------	------------------------	------------------