



## Dieselmotive 175 20W-40

Product Code:78430

Diesel Locomotive Engine Oil

**Dieselmotive 175 20W-40** is a high performance, zinc-free and chlorine-free oil specially designed to provide excellent engine cleanliness and oil filter life in the modern railroad diesel locomotive engines.

**Dieselmotive 175 20W-40** is based on high quality virgin mineral base oil in combination with an unique additive package to ensure the following properties:

- Exceptional detergency and dispersancy provides excellent engine cleanliness, especially engine top decks.
- Excellent retention of TBN facilitates extended drain intervals.
- High thermo-oxidative.
- Zinc-free formulation protects silver bearings against corrosion.
- Non-chlorinated additive package helps in reducing used oil disposal costs.

**Dieselmotive 175 20W-40** exceeds the following performance criteria:

API CF / CF-2	LMOA Generation 5	EMD of General Motors
GE as Generation 4 Long Life Oils		GE Diesel Engines

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J 300	20W-40
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	877.0
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	128.5
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	15.2
Viscosity Index		ASTM D2270	122
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-30
Total Base Number	mgKOH/g	ASTM D2896	17.5
Sulphated Ash	%Wt	ASTM D874	1.5

Date Issued: 10-12-2024	Supersedes: 03-03-2021	Revision Nr.: 02
-------------------------	------------------------	------------------