

Motor Oil Synthetic SN 10W-40

Motor Oil Synthetic SN 10W-40 is an universal high performance fuel saving synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for engines equipped with a Particulate Filter.

Product Code: 79050

Motor Oil Synthetic SN 10W-40 is formulated with high quality synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

Motor Oil Synthetic SN 10W-40 meets the following performance criteria:

Approved MB-Approval 229.3

Meets API SP ACEA A3/B4 MB 226.5

RN 0700/0710 VW 501.01/505.00

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-40
Density @15°C	kg/m ³	ASTM D4052	860.1
Kin. Viscosity @40°C	mm²/s	ASTM D7042	90.8
Kin. Viscosity @100°C	mm²/s	ASTM D7042	13.8
Viscosity Index		ASTM D2270	155
Viscosity CCS @-25°C	cР	ASTM D5293	5980
Flash Point COC, min	°C	ASTM D92	>215
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	11.3
Sulphated Ash	%Wt	ASTM D874	1.3